
SODAR Core Documentation

Release 0.7.2

Mikko Nieminen

Jan 31, 2020

CONTENTS:

1	SODAR Core Overview and Example Use Case	3
1.1	SODAR Core Overview	3
1.2	Example Use Case	3
1.3	Next Steps	5
2	Glossary	7
3	Getting Started	9
3.1	Installation	9
3.2	SODAR Core Apps	9
3.3	Requirements	9
3.4	Next Steps	10
4	Projectroles App	11
4.1	Projectroles Basics	11
4.2	Projectroles Integration	13
4.3	Projectroles Django Settings	18
4.4	Projectroles Usage	25
4.5	Projectroles Customization	33
4.6	Projectroles API Documentation	35
5	Adminalerts App	49
5.1	Basics	49
5.2	Installation	49
5.3	Usage	50
6	Bgjobs App	51
6.1	Bgjobs Installation	51
6.2	Bgjobs Usage	52
7	Filesfolders App	53
7.1	Filesfolders Installation	53
7.2	Filesfolders Usage	54
8	Userprofile App	57
8.1	Installation	57
8.2	Usage	58
8.3	User Settings	58
9	Siteinfo App	59
9.1	Basics	59

9.2	Installation	59
9.3	Usage	60
10	Sodarcache App	61
10.1	Sodarcache Installation	61
10.2	Sodar Cache Usage	62
10.3	Sodarcache Backend API Documentation	64
11	Taskflow Backend	67
11.1	Basics	67
11.2	Installation	67
11.3	Usage	68
11.4	API Documentation	68
12	Timeline App	71
12.1	Timeline Installation	71
12.2	Timeline Usage	72
12.3	Timeline API Documentation	75
13	Development	81
13.1	General Development Topics	81
13.2	Project App Development	82
13.3	Site App Development	95
13.4	Backend App Development	98
13.5	SODAR Core Development	100
14	Major Changes	103
14.1	v0.7.2 (2020-01-31)	103
14.2	v0.7.1 (2019-12-18)	104
14.3	v0.7.0 (2019-10-09)	105
14.4	v0.6.2 (2019-06-21)	106
14.5	v0.6.1 (2019-06-05)	106
14.6	v0.6.0 (2019-05-10)	106
14.7	v0.5.1 (2019-04-16)	107
14.8	v0.5.0 (2019-04-03)	108
14.9	v0.4.5 (2019-03-06)	109
14.10	v0.4.4 (2019-02-19)	110
14.11	v0.4.3 (2019-01-31)	110
14.12	v0.4.2 (2019-01-25)	111
14.13	v0.4.1 (2019-01-11)	112
14.14	v0.4.0 (2018-12-19)	112
14.15	v0.3.0 (2018-10-26)	113
15	SODAR Core Changelog	115
15.1	v0.7.2 (2020-01-31)	115
15.2	v0.7.1 (2019-12-18)	116
15.3	v0.7.0 (2019-10-09)	118
15.4	v0.6.2 (2019-06-21)	120
15.5	v0.6.1 (2019-06-05)	121
15.6	v0.6.0 (2019-05-10)	122
15.7	v0.5.1 (2019-04-16)	123
15.8	v0.5.0 (2019-04-03)	125
15.9	v0.4.5 (2019-03-06)	126
15.10	v0.4.4 (2019-02-19)	126
15.11	v0.4.3 (2019-01-31)	127

15.12 v0.4.2 (2019-01-25)	128
15.13 v0.4.1 (2019-01-11)	129
15.14 v0.4.0 (2018-12-19)	131
15.15 v0.3.0 (2018-10-26)	132
15.16 v0.2.1 (2018-09-20)	134
15.17 v0.2.0 (2018-09-19)	134
15.18 v0.1.0 (2018-09-12)	135
16 Indices and tables	139
Python Module Index	141
Index	143

This documentation provides instructions for SODAR Core usage, integration and development. SODAR Core is framework for project access control and project application management, also including multiple optional applications for aiding project work. SODAR Core is built on the [Django](#) web framework.

SODAR (System for Omics Data Access and Retrieval) is a specialized system for managing data in omics research projects, which was the origin of the components in this package.

The **SODAR Core** package contains the core functionality for the SODAR system along with reusable and non-domain-specific web apps. The package and its apps can be used in any Django-based web site which wants to make use of one or more of the following features:

- Project-based user access control
- Dynamic app content management
- Advanced project activity logging
- Small file uploading and browsing
- Managing server-side background jobs
- Caching and aggregation of data from external services
- Tracking site information and statistics

Basics of Django site setup and instructions for third party packages used are considered out of scope for this documentation. Basic knowledge of the Django framework is assumed. For this, please refer to the [official Django documentation](#) and/or docs of related third party packages.

NOTE: To view this document in the rendered form during development, run `make html` in the `docs` directory of the repository. You can find the rendered HTML in `docs/build`. You will have to install system and Python dependencies, including ones in `requirements/local.txt` for this to work. See [SODAR Core Development](#).

SODAR CORE OVERVIEW AND EXAMPLE USE CASE

This document presents an overview of the SODAR Core package along with an example use case.

1.1 SODAR Core Overview

The SODAR Core package provides a suite of *Django apps* to be installed on a *Django-based web site*. The main app in the package, `projectroles`, provides core project access, content management framework and default UI templates for other apps on the site. Those apps must implement or use specific parts of the `projectroles` app to enable desired SODAR Core functionality.

Apps in a SODAR Core based site are separated into *project*, *site* and *backend* apps, depending on their scope and purpose. The SODAR Core package includes optional general purpose apps of each type, which the user may enable on their site if needed. These apps all depend on `projectroles`. More on the general purpose apps can be found in the *Getting Started* document.

To build their own web based system with SODAR Core, the user will develop required functionality and UIs as one or more Django apps, using and extending functionalities offered by the `projectroles` app and optional backend apps. This allows integration of the app into the project access management, standardized layout and other features such as advanced logging. Furthermore, the `projectroles` app will call certain functions implemented in the user's apps to dynamically include app and project content in Django views. In addition to developing new Django apps, existing apps can be easily modified to gain access to SODAR Core features.

1.2 Example Use Case

In a typical scenario for SODAR Core use, a research organization wants to develop a user friendly system for accessing, browsing and/or manipulating research data. The data may belong to several different projects, with different research groups or scientists working on it. This data may be confidential in nature, so access control is required, preferably using the organization's existing LDAP/AD servers. The organization wants to provide a web-based GUI as well as programmatic API views.

1.2.1 Site Setup

First the developer will *set up a SODAR Core based Django site*. This can be created from a SODAR Core site template or by integrating the `django-sodar-core` package on an existing site. The Django site must be configured according to organization requirements, e.g. setting up user access via the organization LDAP/AD server.

The initial SODAR Core integration into a Django site adds e.g. a general layout, organization of apps and content into projects as well as project-based access control.




Fig. 1: Structure of a SODAR Core based web site

1.2.2 App Development

Next the developer needs to *develop the Django app(s)* which contain the actual program logic and user interfaces required for the use case. The content or number of these apps are not restricted by SODAR Core. Anything which would go to a typical Django app is OK, as long as certain building blocks for SODAR Core functionality are used.

Optional applications bundled with SODAR Core can also be enabled or disabled at this point. for example, if involved projects require sharing and storage of reports and presentations, the developer may select to enable the *filesfolders* app. Likewise, if detailed logging or audit trails are needed, the developer can enable the *timeline* app.

1.2.3 User and Project Setup

Once the site is deployed, the developer should *create initial project categories* and provide access to those for high level personnel such as project owners. The owners can then go on and create relevant projects, grant access to researchers and set up initial data in the applications.

1.2.4 Using the Site

The researchers will log in to the site on their web browser, in most cases using the standard LDAP credentials provided by their organization. They will see the projects they have been granted access to and can use whichever applications have been enabled or developed for the site, according to their assigned user rights. SODAR Core provides common navigation, overview and search views for all enabled apps, including the one(s) developed by the organization. The same user access management features are shared for all apps, along with possible REST APIs developed by the organization.

1.3 Next Steps

See the *Getting Started* document for instructions on installing SODAR Core and how to proceed with developing your own SODAR Core based site.

GLOSSARY

App Plugin Mechanism for defining common properties and operations for dynamically including content and functionality from apps in SODAR Core views.

App Settings Project or user specific settings defined in SODAR Core app plugins. Different from e.g. Django settings used to configure the web site.

Backend App SODAR Core application which is used to provide additional functionality to other SODAR Core apps. Does not have its own GUI entry point. Common use cases include APIs to external services or other apps.

Django App Application built for the Django web framework, including (but not limited to) SODAR Core based apps.

Django Settings Django settings used to configure the website. SODAR Core apps also use Django settings for configuring framework and app behaviour.

Django Site Web site built on the Django framework, including (but not limited to) any website based on SODAR Core.

Peer Site A SODAR Core based web site which mirrors one or more projects also mirrored on the currently active site. This allows linking to remote projects on other sites where the user would have access.

Project App SODAR Core application with the scope of providing data and functionality related to a specific project. Uses project-based access control.

SODAR System for Omics Data Access and Retrieval. An omics research data management system which is the origin of the reusable SODAR Core framework.

SODAR Core Core framework and reusable apps originally built for the SODAR project.

SODAR Core App Django application with additional SODAR Core features. This includes one or more app plugin definitions to enable dynamic inclusion of the app into the SODAR Core framework, as well as project access control for project apps.

SODAR Core Based Site Django-based web site using SODAR Core apps as its framework.

Site App SODAR Core application with does not limit its scope to a single project. Common use cases include user account management and administrative tools.

Source Site SODAR Core based web site which mirrors project metadata and access control to “target” sites.

Target Site SODAR Core based web site which mirrors project metadata and access control from a “source” site.

GETTING STARTED

Installation and basic concepts of the SODAR Core framework and its apps are detailed in this document.

3.1 Installation

The `django-sodar-core` package can be installed from GitHub using `pip` as follows. It is strongly recommended to specify a version tag, as the package is under active development and breaking changes can be expected. PyPI install is forthcoming.

```
pip install -e git+https://github.com/bihealth/sodar_core.git@v0.7.2#egg=django-sodar-  
→core
```

Please note that the `django-sodar-core` package only installs *Django apps*, which you need to include in a *Django web site* project. For instructions for integrating SODAR Core into an existing Django site or setting up a new site, see the *projectroles app documentation*.

3.2 SODAR Core Apps

The following Django apps will be installed when installing the `django-sodar-core` package:

- **projectroles**: Base app for project access management and dynamic app content management. All other apps require the integration of `projectroles`.
- **adminalerts**: Site app for displaying site-wide messages to all users.
- **bgjobs**: Project app for managing background jobs.
- **siteinfo**: Site app for displaying site information and statistics for administrators.
- **sodarcache**: Generic caching and aggregation of data referring to external services.
- **taskflowbackend**: Backend app providing an API for the optional `sodar_taskflow` transaction service.
- **timeline**: Project app for logging and viewing project-related activity.
- **userprofile**: Site app for viewing user profiles.

3.3 Requirements

Major requirements for integrating `projectroles` and other SODAR Core apps into your Django site are listed below. For a complete requirement list, see the `requirements` and `utility` directories in the repository.

- Ubuntu (16.04 Xenial recommended and supported) / CentOS 7
- System library requirements (see the `utility` directory and/or your own Django project)
- Python 3.6 (**NOTE:** Python 3.5 no longer supported)
- Django 1.11 (**NOTE:** 2.x not currently supported)
- PostgreSQL 9.6+ and psycopg2-binary
- Bootstrap 4
- JQuery 3.3.x
- Shepherd and Tether
- Clipboard.js
- DataTables

For more details on installation and requirements for local development, see [SODAR Core Development](#).

3.4 Next Steps

To proceed with using the SODAR Core framework in your Django site, you must first install and integrate the `projectroles` app. See the [projectroles app documentation](#) for instructions.

Once `projectroles` has been integrated into your site, you may proceed to install other apps as needed.

PROJECTROLES APP

The `projectroles` app is the base app for building a *SODAR Core based Django site*. It provides a framework for project access management, dynamic content retrieval, models and tools for SODAR-compatible apps plus a default template and CSS layout.

Other Django apps which intend to use aforementioned functionalities depend on `projectroles`. While inclusion of other SODAR Core apps can be optional, having `projectroles` installed is **mandatory** for working with the SODAR Core project and app structure.

4.1 Projectroles Basics

The basic concepts and functionalities of the `projectroles` app are detailed in this document.

4.1.1 Projects

The `projectroles` app groups project-specific data, user access roles and other features into **projects** and **categories**. These can be nested in a tree structure with the `category` type working as a container for sub-projects with no project content of its own.

4.1.2 User Roles in Projects

User access to projects is granted by per-project assigning of roles. In each project, a user can have one role at a time. New types of roles can be defined by extending the default model's database table.

The default setup of role types used in SODAR sites:

- **Project Owner**
 - Full read/write access to project data and roles
 - Can create sub-projects under owned categories
 - One per project
 - Must be specified upon project creation
- **Project Delegate**
 - Full read/write access to project data
 - Can modify roles except for owner and delegate
 - One per project (by default, the limit can be increased in site settings)
 - Assigned by owner

- **Project Contributor**
 - Can read and write project data
 - Can modify and delete own data
- **Project Guest**
 - Read only access to project data

Note: Django **superuser** status overrides project role access.

The projectroles app provides the following features for managing user roles in projects:

- Adding/modifying/removing site users as project members
- Inviting people not yet using the site by email
- Automated emailing of users regarding role changes
- Mirroring user roles to/from an external projectroles-enabled site

Note: Currently, only superusers can assign owner roles for top-level categories.

4.1.3 Remote Project Sync

SODAR Core allows optionally reading and synchronizing project metadata between multiple SODAR-based Django sites. A superuser is able to set desired levels of remote access for specific sites on a per-project basis.

A SODAR site can have one of three modes: **source**, **target** or **peer** mode. A SODAR site can be set by the user in either **source** or **target** mode.

- **Source site** is one expecting to (potentially) serve project metadata to an arbitrary number of other SODAR sites.
- **Target site** can be linked with exactly one source site, from which it can retrieve project metadata. Creation of local projects can be enabled or disabled according to local configuration.
- **Peer** mode is used only if two or more Target sites link to the same Source site. If synchronizing a project which has multiple accessing Target sites, metadata about those other Target sites is included and stored in Peer mode site objects.

Among the data which can be synchronized:

- General project information such as title, description and readme
- Project category structure
- User roles in projects
- User accounts for LDAP/AD users (required for the previous step)
- Information of other Target Sites linking a common project

4.1.4 Rule System

Projectroles uses the [django-rules](#) package to manage permissions for accessing data, apps and functionalities within projects based on the user role. Predicates for project roles are provided by the projectroles app and can be used and extended for developing rules for your other project-specific Django apps.

4.1.5 App Plugins

Projectroles provides a plugin framework to enable integrating apps and content dynamically to a projectroles-enabled Django site. Types of apps and corresponding app plugins currently included:

- **Project apps:** Apps related to specific projects, making use of project access control and providing data and content within the project's scope
- **Site apps:** Site-wide Django apps which are not project-specific
- **Backend apps:** Backend apps without a GUI entry point, imported and used dynamically by other SODAR-based apps for e.g. connectivity to external resources.

App plugins are not limited to one per Django app. A single Django app in SODAR Core may contain one or more of the aforementioned plugin types, depending on the required functionality.

Existing apps can be modified to conform to the plugin structure by implementing certain variables, functions, views and templates within the app. For more details, see the app development documents.

4.1.6 Other Features

Other features in the projectroles app:

- **App settings:** Setting values for project or user specific variables, which can be defined in project and site app plugins
- **Project starring:** Ability for users to star projects as their favourites
- **Project search:** Functionality for searching data within projects using functions implemented in project app plugins
- **Tour help:** Inline help for pages
- **Project readme:** README document for each project with Markdown support
- **Custom user model:** Additions to the standard Django user model
- **Multi-domain LDAP/AD support:** Support for LDAP/AD users from multiple domains
- **SODAR Taskflow and Timeline integration:** Included but disabled unless backend apps for Taskflow and Timeline are integrated in the Django site

4.1.7 Templates and Styles

Projectroles provides views and templates for all GUI-related functionalities described above. The templates utilize the plugin framework to provide content under projects dynamically. The project also provides default CSS stylings, base templates and a base layout which can be used or adapted as needed. See the usage and app development documentation for more details.

4.2 Projectroles Integration

This document provides instructions and guidelines for integrating projectroles and other SODAR Core apps into your Django site.

4.2.1 Installation on a New Site

If you want to set up a new Django site for integrating projectroles, see the recommended options in this section.

SODAR Django Site Template (Recommended)

When setting up a new *SODAR Core based site*, it is strongly recommended to use `sodar_django_site` as the template. The repository contains a minimal *Django site* pre-configured with projectroles and other *SODAR Core apps*. The master branch of this project always integrates the latest stable release of SODAR Core and projectroles.

To set up your site with this template, clone the repository and follow the installation instructions in the `README.rst` file.

To modify default SODAR Core and projectroles settings, see the *Projectroles Django Settings* document.

Once you have your site set up, you can look into *customization tips* and start *developing your SODAR Core compatible apps*.

Cookiecutter-Django

If the SODAR Django site template does not suit your needs, it is also possible to set up your site using `cookiecutter-django`. In this case, follow the instructions in the following section as if you were integrating SODAR Core to an existing Django site.

Warning: Currently, SODAR Core only supports Django 1.11.x, while the latest versions of cookiecutter-django set up Django 2.0.x by default. It is strongly recommended to use Django 1.11 LTS for time being. Compatibility with 2.0 and upwards is not guaranteed! Integration into the last official [1.11 release](#) of cookiecutter-django has been tested and verified to be working.

Note: The latest cookiecutter-django 1.11 release has dependencies which are already out of date. Please update them to match the requirements of the `django-sodar-core` package.

Note: For any other issues regarding the cookiecutter-django setup, see the cookiecutter-django documentation.

4.2.2 Installation on an Existing Site

Instructions for setting up projectroles and SODAR Core on an existing Django site or a fresh site generated with cookiecutter-django are detailed in this chapter.

Warning: In order to successfully set up projectroles, you are expected to **follow all the instructions here in the order they are presented**. Please note that leaving out steps may result in a non-working Django site! Attempting to run the site before following all of the steps may (and probably will) result in errors.

Warning: The rest of this section assumes that your Django project has been set up using a [1.11 release](#) of `cookiecutter-django`. Otherwise details such as directory structures and settings variables may differ.

First, add the `django-plugins` and `django-sodar-core` package requirements into your `requirements/base.txt` file. Make sure you are pointing to the desired release tag.

```
-e git://github.com/mikkonie/django-plugins.  
→git@1bc07181e6ab68b0f9ed3a00382eb1f6519e1009#egg=django-plugins  
-e git://github.com/bihealth/sodar_core.git@v0.7.1#egg=django-sodar-core
```

Install the requirements for development:

```
$ pip install -r requirements/local.txt
```

If any version conflicts arise between `django-sodar-core` and your existing site, you will have to resolve them before continuing.

Hint: You can always refer to either the `sodar_django_site` repository or `example_site` in the SODAR Core repository for a working example of a Cookiecutter-based Django site integrating SODAR Core. However, note that some aspects of the site configuration may vary depending on the `cookiecutter-django` version used on your site.

Django Settings

Next you need to modify your default *Django settings* file, usually located in `config/settings/base.py`. For sites created with an older `cookiecutter-django` version the file name may also be `common.py`. Naturally, you should make sure no settings in other configuration files conflict with ones set here.

For values retrieved from environment variables, make sure to configure your `env` accordingly. For development and testing, using `READ_DOT_ENV_FILE` is recommended.

Required and optional Django settings are described in the *Projectroles Django Settings* document.

User Configuration

In order for SODAR Core apps to work on your Django site, you need to extend the default user model.

Extending the User Model

In a `cookiecutter-django` based project, an extended user model should already exist in `{SITE_NAME}/users/models.py`. The abstract model provided by the `projectroles` app provides the same model with critical additions, most notably the `sodar_uuid` field used as an unique identifier for SODAR objects including users.

If you have not added any of your own modifications to the model, you can simply **replace** the existing model extension with the following code:

```
from projectroles.models import SODARUser  
  
class User(SODARUser):  
    pass
```

If you need to include your own extra fields or functions (or have existing ones already), you can add them in this model.

After updating the user model, create and run database migrations.

```
$ ./manage.py makemigrations
$ ./manage.py migrate
```

Note: You probably will need to edit the default unit tests under `{SITE_NAME}/users/tests/` for them to work after making these changes. See `example_site.users.tests` in this repository for an example.

Populating UUIDs for Existing Users

When integrating projectroles into an existing site with existing users, the `sodar_uuid` field needs to be populated. See [instructions in Django documentation](#) on how to create the required migrations.

Synchronizing User Groups for Existing Users

To set up user groups for existing users, run the `syncgroups` management command.

```
$ ./manage.py syncgroups
```

User Profile Site App

The `userprofile` site app is installed with SODAR Core. It adds a user profile page in the user dropdown. Use of the app is not mandatory but recommended, unless you are already using some other user profile app. See the [userprofile app documentation](#) for instructions.

Add Login Template

You should add a login template to `{SITE_NAME}/templates/users/login.html`. If you're OK with using the projectroles login template, the file can consist of the following line:

```
{% extends 'projectroles/login.html' %}
```

If you intend to use projectroles templates for user management, you can delete other existing files within the directory.

URL Configuration

In the Django URL configuration file, usually found in `config/urls.py`, add the following lines under `urlpatterns` to include projectroles URLs in your site.

```
urlpatterns = [
    # ...
    url(r'^api/auth/', include('knox.urls')),
    url(r'^project/', include('projectroles.urls')),
]
```

If you intend to use projectroles views and templates as the basis of your site layout and navigation (which is recommended), also make sure to set the site's home view accordingly:

```
from projectroles.views import HomeView

urlpatterns = [
    # ...
    url(r'^$', HomeView.as_view(), name='home'),
]
```

Finally, make sure your login and logout links are correctly linked. You can remove any default allauth URLs if you're not using it.

```
from django.contrib.auth import views as auth_views

urlpatterns = [
    # ...
    url(r'^login/$', auth_views.LoginView.as_view(
        template_name='users/login.html'), name='login'),
    url(r'^logout/$', auth_views.logout_then_login, name='logout'),
]
```

Base Template for Your Django Site

In order to make use of Projectroles views and templates, you should set the base template of your site accordingly in `{SITE_NAME}/templates/base.html`.

For a supported example, see `projectroles/base_site.html`. It is strongly recommended to use this as the base template for your site, either by extending it or copying the content into `{SITE_NAME}/templates/base.html` and modifying it to suit your needs.

If you do not need to make any modifications, the most simple way is to replace the content of the `{SITE_NAME}/templates/base.html` file with the following line:

```
{% extends 'projectroles/base_site.html' %}
```

Note: CSS and Javascript includes in `site_base.html` are **mandatory** for Projectroles-based views and functionalities.

Note: The container structure defined in the example `base.html`, along with including the `{STATIC}/projectroles/css/projectroles.css` are **mandatory** for Projectroles-based views to work without modifications.

Site Error Templates

The projectroles app contains default error templates to use on your site. These are located in the `projectroles/error/` template directory. You can use them by entering `{% extends 'projectroles/error/*.html %}` in the corresponding files found in the `{SITE_NAME}/templates/` directory. You have the options of extending or replacing content on the templates, or simply implementing your own.

All Done!

After following all the instructions above, you should have a working SODAR Core based Django site with support for projectroles features and SODAR Core apps. To test the site locally execute the supplied shortcut script:

```
$ ./run.sh
```

Or, run the standard Django `runserver` command:

```
$ ./manage.py runserver
```

You can now browse your site locally at `http://127.0.0.1:8000`. You are expected to log in to view the site. Use e.g. the superuser account you created when setting up your cookiecutter-django site.

You can now continue on to create apps or modify your existing apps to be compatible with the SODAR Core framework. See the [development section](#) for app development guides. Also see the [customization documentation](#) for tips for modifying the default appearance of SODAR Core.

4.3 Projectroles Django Settings

This document describes the *Django settings* for the `projectroles` app, which also control the configuration of other apps in a SODAR Core based site.

These settings are usually found in `config/settings/*.py`, with `config/settings/base.py` being the default configuration other files may override or extend.

If your site is based on `sodar_django_site`, mandatory settings are already set to their default values. In that case, you only need to modify or customize them where applicable.

If you are integrating `django-sodar-core` with an existing Django site or building your site from scratch without the recommended template, make sure to add all mandatory settings into your project.

For values retrieved from environment variables, make sure to configure your env accordingly. For development and testing, it is highly recommended to set `DJANGO_READ_DOT_ENV_FILE=1` in your system's environment variables and place the env variables into a `.env` file in the root directory of your Django site repository. See `env.example` for an example of such a file.

4.3.1 Site Package and Paths

The site package and path configuration should be found at the beginning of the default configuration file. Substitute `{SITE_NAME}` with the name of your site package.

```
import environ
SITE_PACKAGE = '{SITE_NAME}'
ROOT_DIR = environ.Path(__file__) - 3
APPS_DIR = ROOT_DIR.path(SITE_PACKAGE)
```

4.3.2 Apps

Apps installed from `django-sodar-core` are placed in `THIRD_PARTY_APPS`. The following apps need to be included in the list in order for SODAR Core to work:


```

THIRD_PARTY_APPS = [
    # ...
    'crispy_forms',
    'rules.apps.AutodiscoverRulesConfig',
    'djangoplugins',
    'pagedown',
    'markupfield',
    'rest_framework',
    'knox',
    'projectroles.apps.ProjectrolesConfig',
    'dal',
    'dal_select2',
]

```

4.3.3 Database

Under DATABASES, the setting below is recommended:

```
DATABASES['default']['ATOMIC_REQUESTS'] = False
```

Note: If this conflicts with your existing set up, you can modify the code in your other apps to use e.g. `@transaction.atomic`.

Note: This setting mostly is used for the `sodar_taskflow` transactions supported by `projectroles` but not commonly used, so having this setting as `True` *may* cause no issues. However, it is not officially supported at this time.

4.3.4 Templates

Under `TEMPLATES['OPTIONS']['context_processors']`, add the `projectroles` URLs processor:

```
'projectroles.context_processors.urls_processor',
```

4.3.5 Email

Under `EMAIL_CONFIGURATION` or `EMAIL`, configure email settings:

```

EMAIL_SENDER = env('EMAIL_SENDER', default='noreply@example.com')
EMAIL_SUBJECT_PREFIX = env('EMAIL_SUBJECT_PREFIX', default='')

```

4.3.6 Authentication

`AUTHENTICATION_BACKENDS` should contain the following backend classes:

```

AUTHENTICATION_BACKENDS = [
    'rules.permissions.ObjectPermissionBackend',
    'django.contrib.auth.backends.ModelBackend',
]

```

Note: The default setup by cookiecutter-django adds the `allauth` package. This can be left out of the project if not needed, as it mostly provides adapters for e.g. social media account logins. If removing `allauth`, you can also remove unused settings variables starting with `ACCOUNT_*`.

The following settings remain in your auth configuration:

```
AUTH_USER_MODEL = 'users.User'
LOGIN_REDIRECT_URL = 'home'
LOGIN_URL = 'login'
```

4.3.7 Django REST Framework

To enable `django-rest-framework` API views and `knox` authentication, these values should be added under `DEFAULT_AUTHENTICATION_CLASSES`:

```
REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': (
        'rest_framework.authentication.BasicAuthentication',
        'rest_framework.authentication.SessionAuthentication',
        'knox.auth.TokenAuthentication',
    ),
}
```

4.3.8 General Site Settings

For display in `projectroles` based templates, customize related variables to describe your site. `SITE_INSTANCE_TITLE` may be used to e.g. differentiate between site versions used for deployment or staging, use in different organizations, etc.

```
SITE_TITLE = 'Name of Your Project'
SITE_SUBTITLE = env.str('SITE_SUBTITLE', 'Beta')
SITE_INSTANCE_TITLE = env.str('SITE_INSTANCE_TITLE', 'Deployment Instance Name')
```

4.3.9 Projectroles Settings

Mandatory `projectroles` app settings are explained below:

- `PROJECTROLES_SITE_MODE`: Site mode for remote project metadata synchronization, either `SOURCE` (allow others to read local projects) or `TARGET` (read projects from another site)
- `PROJECTROLES_TARGET_CREATE`: Whether or not local projects can be created if site is in `TARGET` mode. If your site is in `SOURCE` mode, this setting has no effect.
- `PROJECTROLES_INVITE_EXPIRY_DAYS`: Days until project email invites expire (int)
- `PROJECTROLES_SEND_EMAIL`: Enable/disable email sending (bool)
- `PROJECTROLES_EMAIL_SENDER_REPLY`: Whether replies are expected to the sender address (bool). If set `False` and nothing is set in the `reply-to` header, a “do not reply” note is added to the email body.
- `PROJECTROLES_ENABLE_SEARCH`: Whether you want to enable SODAR search on your site (boolean)
- `PROJECTROLES_DEFAULT_ADMIN`: User name of the default superuser account used in e.g. replacing an unavailable user or performing backend admin commands (string)

Example:

```
# Projectroles app settings
PROJECTROLES_SITE_MODE = env.str('PROJECTROLES_SITE_MODE', 'TARGET')
PROJECTROLES_TARGET_CREATE = env.bool('PROJECTROLES_TARGET_CREATE', True)
PROJECTROLES_INVITE_EXPIRY_DAYS = env.int('PROJECTROLES_INVITE_EXPIRY_DAYS', 14)
PROJECTROLES_SEND_EMAIL = env.bool('PROJECTROLES_SEND_EMAIL', False)
PROJECTROLES_EMAIL_SENDER_REPLY = env.bool('PROJECTROLES_EMAIL_SENDER_REPLY', False)
PROJECTROLES_ENABLE_SEARCH = True
PROJECTROLES_DEFAULT_ADMIN = env.str('PROJECTROLES_DEFAULT_ADMIN', 'admin')
```

4.3.10 Optional Projectroles Settings

The following projectroles settings are **optional**:

- **PROJECTROLES_SECRET_LENGTH**: Character length of secret token used in projectroles (int)
- **PROJECTROLES_SEARCH_PAGINATION**: Amount of search results per each app to display on one page (int)
- **PROJECTROLES_HELP_HIGHLIGHT_DAYS**: Days for highlighting tour help for new users (int)
- **PROJECTROLES_DISABLE_CATEGORIES**: If set True, disable categories and only allow a list of projects on the root level (boolean) (see note)
- **PROJECTROLES_HIDE_APP_LINKS**: Apps hidden from the project sidebar and dropdown menus for non-superusers. The app views and URLs are still accessible. The names should correspond to the name property in each project app's plugin (list)
- **PROJECTROLES_DELEGATE_LIMIT**: The number of delegate roles allowed per project. The amount is limited to 1 per project if not set, unlimited if set to 0. Will be ignored for remote projects synchronized from a source site (int)
- **PROJECTROLES_BROWSER_WARNING**: If true, display a warning to users using Internet Explorer (bool)
- **PROJECTROLES_ALLOW_LOCAL_USERS**: If true, roles for local non-LDAP users can be synchronized from a source during remote project sync if they exist on the target site. Similarly, local users will be selectable in member dropdowns when selecting users (bool)
- **PROJECTROLES_KIOSK_MODE**: If true, allow accessing certain project views *without* user authentication in order to e.g. demonstrate features in a kiosk-style deployment. Also hides and/or disables views not intended to be used in this mode (bool)

Example:

```
# Projectroles app settings
# ...
PROJECTROLES_SECRET_LENGTH = 32
PROJECTROLES_SEARCH_PAGINATION = 5
PROJECTROLES_HELP_HIGHLIGHT_DAYS = 7
PROJECTROLES_DISABLE_CATEGORIES = True
PROJECTROLES_HIDE_APP_LINKS = ['filesfolders']
PROJECTROLES_DELEGATE_LIMIT = 1
PROJECTROLES_BROWSER_WARNING = True
PROJECTROLES_ALLOW_LOCAL_USERS = True
PROJECTROLES_KIOSK_MODE = False
```

Warning: Regarding `PROJECTROLES_DISABLE_CATEGORIES`: In the current SODAR core version remote site access and remote project synchronization are disabled if this option is used! Use only if a simple project list is specifically required in your site.

Warning: Regarding `PROJECTROLES_ALLOW_LOCAL_USERS`: Please note that this will allow synchronizing project roles to local non-LDAP users based on their **user name**. You should personally ensure that the users in question are authorized for these roles. Furthermore, only roles for **existing** local users will be synchronized. New local users will have to be added manually through the Django admin or shell on the target site.

Warning: The `PROJECTROLES_KIOSK_MODE` setting is under development and considered experimental. More implementation, testing and documentation is forthcoming.

4.3.11 Backend App Settings

The `ENABLED_BACKEND_PLUGINS` settings lists backend plugins implemented using `BackendPluginPoint` which are enabled in the configuration. For more information see [Backend App Development](#).

```
ENABLED_BACKEND_PLUGINS = env.list('ENABLED_BACKEND_PLUGINS', None, [])
```

4.3.12 API View Settings (Optional)

If you want to build an API to your site using SODAR Core functionality, it is recommended to base your API views on `projectroles.views.SODARAPIBaseView`. Using this base class also allows you to define your API media type, version number and allowed versions via Django settings.

The recommended API setup uses accept header versioning. The `SODAR_API_MEDIA_TYPE` setting should be changed to your organization and API identification if API views are introduced. The `SODAR_API_DEFAULT_HOST` setting should post to the externally visible host of your server and be configured in your environment settings.

These settings are **optional**. Default values will be used if they are unset.

Example:

```
SODAR_API_DEFAULT_VERSION = '0.1'
SODAR_API_ACCEPTED_VERSIONS = [SODAR_API_DEFAULT_VERSION]
SODAR_API_MEDIA_TYPE = 'application/your.application+json' # Change this
SODAR_API_DEFAULT_HOST = SODAR_API_DEFAULT_HOST = env.url('SODAR_API_DEFAULT_HOST',
↪ 'http://0.0.0.0:8000')
```

4.3.13 LDAP/AD Configuration (Optional)

If you want to utilize LDAP/AD user logins as configured by `projectroles`, you can add the following configuration. Make sure to also add the related env variables to your configuration.

This part of the setup is **optional**.

Note: In order to support LDAP, make sure you have installed the dependencies from `utility/install_ldap_dependencies.sh` and `requirements/ldap.txt`! For more information see [SODAR Core Development](#).

Note: If only using one LDAP/AD server, you can leave the “secondary LDAP server” values unset.

```
ENABLE_LDAP = env.bool('ENABLE_LDAP', False)
ENABLE_LDAP_SECONDARY = env.bool('ENABLE_LDAP_SECONDARY', False)

if ENABLE_LDAP:
    import itertools
    import ldap
    from django_auth_ldap.config import LDAPSearch

    # Default values
    LDAP_DEFAULT_CONN_OPTIONS = {ldap.OPT_REFERRALS: 0}
    LDAP_DEFAULT_FILTERSTR = '(sAMAccountName=%(user)s)'
    LDAP_DEFAULT_ATTR_MAP = {
        'first_name': 'givenName',
        'last_name': 'sn',
        'email': 'mail',
    }

    # Primary LDAP server
    AUTH_LDAP_SERVER_URI = env.str('AUTH_LDAP_SERVER_URI', None)
    AUTH_LDAP_BIND_DN = env.str('AUTH_LDAP_BIND_DN', None)
    AUTH_LDAP_BIND_PASSWORD = env.str('AUTH_LDAP_BIND_PASSWORD', None)
    AUTH_LDAP_CONNECTION_OPTIONS = LDAP_DEFAULT_CONN_OPTIONS

    AUTH_LDAP_USER_SEARCH = LDAPSearch(
        env.str('AUTH_LDAP_USER_SEARCH_BASE', None),
        ldap.SCOPE_SUBTREE,
        LDAP_DEFAULT_FILTERSTR,
    )
    AUTH_LDAP_USER_ATTR_MAP = LDAP_DEFAULT_ATTR_MAP
    AUTH_LDAP_USERNAME_DOMAIN = env.str('AUTH_LDAP_USERNAME_DOMAIN', None)
    AUTH_LDAP_DOMAIN_PRINTABLE = env.str(
        'AUTH_LDAP_DOMAIN_PRINTABLE', AUTH_LDAP_USERNAME_DOMAIN
    )

    AUTHENTICATION_BACKENDS = tuple(
        itertools.chain(
            ('projectroles.auth_backends.PrimaryLDAPBackend',),
            AUTHENTICATION_BACKENDS,
        )
    )

    # Secondary LDAP server (optional)
    if ENABLE_LDAP_SECONDARY:
        AUTH_LDAP2_SERVER_URI = env.str('AUTH_LDAP2_SERVER_URI', None)
        AUTH_LDAP2_BIND_DN = env.str('AUTH_LDAP2_BIND_DN', None)
        AUTH_LDAP2_BIND_PASSWORD = env.str('AUTH_LDAP2_BIND_PASSWORD', None)
        AUTH_LDAP2_CONNECTION_OPTIONS = LDAP_DEFAULT_CONN_OPTIONS
```

(continues on next page)

(continued from previous page)

```

AUTH_LDAP2_USER_SEARCH = LDAPSearch(
    env.str('AUTH_LDAP2_USER_SEARCH_BASE', None),
    ldap.SCOPE_SUBTREE,
    LDAP_DEFAULT_FILTERSTR,
)
AUTH_LDAP2_USER_ATTR_MAP = LDAP_DEFAULT_ATTR_MAP
AUTH_LDAP2_USERNAME_DOMAIN = env.str('AUTH_LDAP2_USERNAME_DOMAIN')
AUTH_LDAP2_DOMAIN_PRINTABLE = env.str(
    'AUTH_LDAP2_DOMAIN_PRINTABLE', AUTH_LDAP2_USERNAME_DOMAIN
)

AUTHENTICATION_BACKENDS = tuple(
    itertools.chain(
        ('projectroles.auth_backends.SecondaryLDAPBackend',),
        AUTHENTICATION_BACKENDS,
    )
)

```

4.3.14 Global JS/CSS Include Modifications (Optional)

It is possible to supplement (or replace, see below) global Javascript and CSS includes of your SODAR Core site without altering the base template. You can place a list of custom includes into the list variables `PROJECTROLES_CUSTOM_JS_INCLUDES` and `PROJECTROLES_CUSTOM_CSS_INCLUDES`. These can either be local static file paths or web URLs to e.g. CDN served files.

If using the default CDN imports for JQuery, Bootstrap4 etc. are not an optimal solution in your use case due to e.g. network issues, you can disable these includes by setting `PROJECTROLES_DISABLE_CDN_INCLUDES` to `True`.

Warning: If disabling the default CDN includes, you **must** provide replacements for **all** disabled files in your custom includes. Otherwise your SODAR Core based site will not function correctly!

Example:

```

PROJECTROLES_DISABLE_CDN_INCLUDES = True
PROJECTROLES_CUSTOM_JS_INCLUDES = [
    STATIC_ROOT + '/your/path/jquery-3.3.1.min.js',
    STATIC_ROOT + '/your/path/popper.min.js',
    'https://some-cdn.com/bootstrap.min.js',
    # ...
]
PROJECTROLES_CUSTOM_CSS_INCLUDES = [
    STATIC_ROOT + '/your/path/bootstrap.min.css',
    STATIC_ROOT + '/your/path/font-awesome.min.css',
    # ...
]

```

4.3.15 Modifying SODAR_CONSTANTS (Optional)

String identifiers used globally in SODAR project management are defined in the `SODAR_CONSTANTS` dictionary. It can be imported into your app code with the import:

```
from projectroles.models import SODAR_CONSTANTS
```

If you need to update or extend the constants for use your site, you can import the default dictionary into your Django settings and modify it as necessary with the following snippet:

```
from projectroles.constants import get_sodar_constants
SODAR_CONSTANTS = get_sodar_constants(default=True)
# Your changes here..
```

Warning: Modifying existing default constants may result in unwanted issues, especially on a site which already contains created projects. Proceed with caution!

4.3.16 Logging (Optional)

It is recommended to add “projectroles” under `LOGGING['loggers']`. For production, INFO debug level is recommended.

4.4 Projectroles Usage

This document provides instructions for using the `projectroles` app which has been integrated into your Django site.

Hint: Detailed instructions for many pages can be found in an interactive tour by clicking the “Help” link in the right side of the top navigation bar.

Before reading this document, be sure to see *Projectroles Basics* for basic concepts regarding the use of this app.


4.4.1 Logging In

Apart from specific public or token-enabled views, user login is **mandatory** for using a SODAR Core based Django site.

One can either log in using a local Django user or, if LDAP/AD is enabled, their LDAP/AD credentials from a supported site. In the latter case, the user domain must be appended to the user name in form of `user@DOMAIN`.

Log In

Please log in.



The login form consists of two input fields and a button. The first field is labeled 'username@DOMAIN' and the second is labeled 'Password'. Below these fields is a blue button with a right-pointing arrow and the text 'Log In'.

Fig. 1: SODAR login form

4.4.2 User Interface

Basics

Upon login into a SODAR Core based Django site using default templates and CSS, the general view of your site is split into the following elements:

- **Top navigation bar:** Contains the site logo and title, search element, help link and the user dropdown menu.
- **User dropdown menu:** Contains links to user management, admin site and site-wide apps the user has access to.
- **Project sidebar:** Shortcuts to project apps and project management pages
- **Project navigation:** Project structure breadcrumb (disabled for site apps)
- **Content:** Actual app content goes in this element
- **Footer:** Optional footer with e.g. site info and version




Fig. 2: Home view

Home View

As content within a SODAR Core based site is by default sorted into projects, the home view displays a tree view of categories and projects to choose from. You can filter the list with a search term or restrict display to your starred projects.

Project Detail View

The project detail page dynamically imports elements from installed project apps, usually showing e.g. overview of latest additions to app data, statistics and/or shortcuts to app functionalities. Here you can also access project apps




Fig. 3: User dropdown

from the project sidebar. For project apps, the sidebar link leads to the app entry point view as defined in the app plugin.

For each page in a project app which extends the default projectroles template layout, the **project title bar** is displayed on the top of the page. This contains the project title and description and a link to “star” the project into your favourites. Below this, the **project app title bar** with possible app-specific controls is usually displayed.

4.4.3 Category and Project Management

In SODAR based sites, data is split into **categories** and **projects**. Categories may be freely nested and are used as containers of projects. They may contain a description and readme, but project apps and user roles beyond owner are disabled for categories. Projects can not be nested within each other.

Creating a Top Level Category

Currently, only users with a superuser status can create a top level category. This can be done by navigating to the *home view* and clicking the **Create Category** link. To create a category, a name and owner must be supplied, along with optional description and/or a readme document. All of these may be modified later.

Note: Currently, only users already previously logged into the system can be added as the owner of a category or project. The ability to invite users not yet on the site as owners will be added later.

Hint: When setting up a new site, think about what kind of category and project structure makes sense for your team and organization. Moving projects and categories under different categories is possible, but is not recommended and can currently only be done via the admin view or directly in the Django shell.




Fig. 4: Project detail view




Fig. 5: Category/project creation form

Creating Projects

Once navigating into a category, a user with sufficient access will see the **Create Project or Category** link in the side bar. This opens up a form for adding a project or a nested category under the current category. The form is identical to top level category creation, except that you can also choose between creating a project or a category.

Updating Projects

An existing project or category can be updated from the **Update Project/Category** link in the side bar. Again, a similar form as before will be presented to the user.

The screenshot displays the 'Update Project' form in the SODAR Core interface. The sidebar on the left contains navigation icons and labels: Home, Project Overview, Small Files, Timeline, Background Jobs, Example Project App, Members, and Update Project. The main content area has a breadcrumb trail: Home / Test Core Category / Test Core Project. The form title is 'Test Core Project' with a star icon and 'Updating description'. Below this is the 'Update Project' heading. The form includes several input fields: 'Title*' (containing 'Test Core Project'), 'Owner*' (a dropdown menu with 'admin' selected), and 'Description' (containing 'This is a test project'). There is also a 'Short description' field. The 'Readme' section features a rich text editor with a toolbar and a text area containing a TODO list: '## TODO', '* Add readme here', and '* Update documentation screenshots'. At the bottom, there is an 'HTML Preview' section.

Fig. 6: Category/project updating form

App Settings

Project and site apps may define *app settings*, which can be either be set with the scope of *project*, *user* or *user within a project*.

Widgets for project specific settings will show up in the project creation and updating form and can only be modified by users with sufficient project access. User specific settings will be displayed in the *Userprofile app*.

By defining the attribute `user_modifiable=False`, project or user app settings will not be shown in the respective project/user update views. This is used e.g. in cases where a project app provides its own UI or updates some “hidden” setting due to user actions. Superusers will still see these hidden settings in the Update Project view.

Settings with the scope of user within a project do not currently have a separate UI of their own. Instead, project apps can produce their own user specific UIs for this functionality if manual user selection is needed.

Note: Currently, project specific app settings are also enabled for categories but do not actually do anything. The behaviour regarding this (remove settings / inherit by nested projects / etc) is TBD.

4.4.4 Member Management

Project member roles can be viewed and modified through the **Project Members** link on the sidebar. Modification requires a sufficient role in the project (owner or delegate) or superuser status.




Fig. 7: Project member list view

Adding Members

There are two ways to add new members to a project:

- **Add Member** is used to add member roles to system users.
- **Invite Member** is used to send email invites to users not yet registered in the system.

Addition or modification of users sends an email notification to the user in question if email sending is enabled on your Django server. The emails can be previewed in corresponding forms.

Hint: As of SODAR Core v0.4.5, it is also possible to create an invite in the “add member” form. Inviting is enabled when inputting an email address not found among the system users.

Modifying Members

Changing or removing user roles can be done from links next to each role on the member list. Project ownership can be transferred to another owner from the dropdown next to the owner role.

Invites

Invites are accepted by the responding user clicking on a link supplied in their invite email and logging in to the site with their LDAP/AD credentials. Invites expire after a certain time and can be reissued or revoked on the **Project Invites** page.

4.4.5 Remote Projects

It is possible to sync project metadata and member roles between multiple SODAR Core based Django sites. Remote sites and access can be managed in the **Remote Site Access** site app, found in the user dropdown menu in the top navigation bar.


Alternatively, remote sites can be created using the following management command:

```
$ ./manage.py addremotesite
```

In the current implementation, your django site must either be in **source** or **target** mode. A source site can define one or multiple target sites where project data can be provided. A target site can define exactly one source site, from which project data can be retrieved from.

Note: These are arbitrary restrictions which may be relaxed in the future, if use cases warrant it.

To enable remote project data reading, you must first set up either a target or a source site depending on the role of your own SODAR site.



SODAR Core Example Site Beta

Search term Search Extra Link Help

Home Create Category

Remote SODAR Sites

+ Add Target Site

Target Sites

Name	URL	Projects	Token	Visible to users	Accessed
Target	http://0.0.0.0:8001/	1	9916vvkciohqw2w45ixfd4ksfgseonci	No	2019-09-02 11:29

Your site is in SOURCE mode.

Fig. 8: Remote site list in source mode

As Source Site

Navigate to the **Remote Site Access** site app and click on the *Add Target Site* link. You will be provided with a form for specifying the remote site. A secret string is generated automatically and you need to provide this to the administrator of the target site in question for accessing your site.

Here you also have the option to hide the remote project link from your users. Users viewing the project on the source site then won't see a link to the target site. Owners and Superusers will still see the link (greyed out). This is most commonly used for internal test sites which only needs to be used by admins.

Once created, you can access the list of projects on your site in regards to the created target site. For each project, you may select an access level, of which three are currently implemented:

- **No access:** No access on the remote site (default)
- **Read roles:** This allows for the target site to read project metadata *and* user roles in order to synchronize project access remotely.
- **Revoked access:** Previously available access which has been revoked. The project will still remain in the target site, but only superusers, the project owner or the project delegate(s) can access it.

Note: The *read roles* access level also provides metadata of the categories above the selected project so that the project structure can be maintained.

Note: Only LDAP/AD user roles and local administrator *owner* roles are provided to the target site. Other local user roles are ignored.

Note: Access levels for purely checking the existence of the project and only reading project metadata (title, description..) without member roles are implemented in the data model and backend, but currently disabled in the UI.

Once desired access to specific projects has been granted and confirmed, the target site will sync the data by sending a request to the source site.




Fig. 9: Remote project list in source mode

As Target Site

The source site should be set up as above using the *Set Source Site* link, using the provided secret string as the access token.

After creating the source site, remote project metadata and member roles (for which access has been granted) can be accessed using the *Synchronize* link. Additionally if the remote Source site is synchronized with multiple Target Sites, information about those other Target sites will be synchronized as well and displayed as *Peer Sites*.

Alternatively, the following management command can be used:

```
$ ./manage.py syncremote
```

Note: If categories or projects with the same name within the same parent exist under a different UUID, they or their child projects will **not** be synchronized.

Note: If a local user is the owner of a synchronized project on the source site, the user defined in the `PROJECTROLES_DEFAULT_ADMIN` will be given the owner role. Hence you **must** have this setting defined if you are implementing a SODAR site in target mode.

4.4.6 Search

The search form is displayed in the top navigation bar if enabled. It currently takes one string as a search parameter, followed by optional keyword argument. At this time, the keyword of `type` has been implemented, used to limit the search to a certain data type as specified in app plugins.

Search results are split into results from different apps. For example, entering `test` will return all objects from all apps containing this string. Alternatively, entering `test type:project` will provide results from any app configured to produce results of type *project*. By default, this will result in the `projectroles` app listing projects which contain the search string in their name and/or description.

Note: Multiple search terms, complex search strings, full-text search and additional keywords/operators will be defined in the future.

4.5 Projectroles Customization

Here you can find some customization instructions and tips for `projectroles` and SODAR Core.

4.5.1 CSS Overrides

If some of the CSS definitions in `{STATIC}/projectroles/css/projectroles.css` do not suit your purposes, it is possible to override them in your own includes. It is still recommended to include the “*Flexbox page setup*” section as provided.

In this chapter are examples of overrides you can place e.g. in `project.css` to change certain defaults.

Hint: While not explicitly mentioned, some parameters may require the `!important` argument to take effect on your site.

Warning: In the future we may instead offer a full Bootstrap 4 theme, which may deprecate current overriding/extending CSS classes.

Static Element Coloring

If you wish to recolor the background of the static elements on the page (title bar, side bar and project navigation breadcrumb), add the following CSS overrides.

```
.sodar-base-navbar, .sodar-pr-sidebar, .sodar-pr-sidebar-nav {  
    background-color: #ff00ff;  
}  
  
.sodar-pr-navbar {  
    background-color: #00ff00;  
}
```

Sidebar Width

If the sidebar is not wide enough for your liking or e.g. a name of an app overflowing, the sidebar can be resized with the following override:

```
.sodar-pr-sidebar {  
    width: 120px;  
}
```

4.5.2 Title Bar

You can implement your own title bar by replacing the default base.html include of projectroles/_site_titlebar.html with your own HTML or include.

When doing this, it is possible to include elements from the default title bar separately:

- Search form: projectroles/_site_titlebar_search.html
- Site app and user operation dropdown: projectroles/_site_titlebar_dropdown.html

See the templates themselves for further instructions.

4.5.3 Additional Title Bar Links

If you want to add additional links *not* related to apps in the title bar, you can implement in the template file {SITE_NAME}/templates/include/_titlebar_nav.html. This can be done for e.g. documentation links or linking to external sites. Example:

```
{# Example extra link #}  
<li class="nav-item">  
    <a href="#" class="nav-link" id="site-extra-link-x" target="_blank">  
        <i class="fa fa-fw fa-question-circle"></i> Extra Link  
    </a>  
</li>
```

4.5.4 Site Icon

An optional site icon can be placed into {STATIC}/images/logo_navbar.png to be displayed in the default Projectroles title bar.

4.5.5 Project Breadcrumb

To add custom content in the end of the default project breadcrumb, use `{% block nav_sub_project_extend %}` in your app template.

The entire breadcrumb element can be overridden by declaring `{% block nav_sub_project %}` block in your app template.

4.5.6 Footer

Footer content can be specified in the optional template file `{SITE_NAME}/templates/include/_footer.html`.

4.5.7 Project and Category Display Names

If the *project* and *category* labels don't match your use case, it is possible to change the labels displayed to the user by editing `SODAR_CONSTANTS` in your Django site settings file. Example:

```
SODAR_CONSTANTS = get_sodar_constants(default=True)
SODAR_CONSTANTS['DISPLAY_NAMES']['CATEGORY'] = {
    'default': 'not-a-category',
    'plural': 'non-categories',
}
SODAR_CONSTANTS['DISPLAY_NAMES']['PROJECT'] = {
    'default': 'not-a-project',
    'plural': 'non-projects',
}
```

See more about overriding `SODAR_CONSTANTS` [here](#).

To print out these values in your views or templates, call the `get_display_name()` function, which is available both as a template tag through `projectroles_common_tags.py` and a general utility function in `utils.py`. Capitalization and pluralization are handled by the function according to arguments. See the [API documentation](#) for details.

Note: These changes will **not** affect role names or IDs and descriptions of Timeline events.

4.6 Projectroles API Documentation

This document contains API documentation for the `projectroles` app. Included are functionalities and classes intended to be used by other applications.

4.6.1 Plugins

SODAR plugin point definitions and helper functions for plugin retrieval are detailed in this section.

Plugin point definitions and plugin API for apps based on projectroles

class `projectroles.plugins.BackendPluginPoint`
 Projectroles plugin point for registering backend apps

get_api()
Return API entry point object.

get_statistics()
Return backend statistics as a dict. Should take the form of {id: {label, value, url (optional), description (optional)}}.

Returns Dict

class projectroles.plugins.**ProjectAppPluginPoint**
Projectroles plugin point for registering project specific apps

get_extra_data_link(*_extra_data*, *_name*)
Return a link for the given timeline label that starts with "extra:".

get_object(*model*, *uuid*)
Return object based on the model class and the object's SODAR UUID.

Parameters

- **model** – Object model class
- **uuid** – sodar_uuid of the referred object

Returns Model object or None if not found

Raise NameError if model is not found

get_object_link(*model_str*, *uuid*)
Return the URL for referring to a object used by the app, along with a label to be shown to the user for linking.

Parameters

- **model_str** – Object class (string)
- **uuid** – sodar_uuid of the referred object

Returns Dict or None if not found

get_project_list_value(*column_id*, *project*, *user*)
Return a value for the optional additional project list column specific to a project.

Parameters

- **column_id** – ID of the column (string)
- **project** – Project object
- **user** – User object (current user)

Returns String (may contain HTML), integer or None

get_statistics()
Return app statistics as a dict. Should take the form of {id: {label, value, url (optional), description (optional)}}.

Returns Dict

get_taskflow_sync_data()
Return data for synchronizing taskflow operations.

Returns List of dicts or None.

search(*search_term*, *user*, *search_type=None*, *keywords=None*)
Return app items based on a search term, user, optional type and optional keywords.

Parameters

- **search_term** – String
- **user** – User object for user initiating the search
- **search_type** – String
- **keywords** – List (optional)

Returns Dict

update_cache (*name=None, project=None, user=None*)

Update cached data for this app, limitable to item ID and/or project.

Parameters

- **name** – Item name to limit update to (string, optional)
- **project** – Project object to limit update to (optional)
- **user** – User object to denote user triggering the update (optional)

urls = []

App URLs (will be included in settings by.djangoplugins)

class projectroles.plugins.**RemoteSiteAppPlugin**

Site plugin for remote site and project management

app_permission = 'userprofile.update_remote'

Required permission for displaying the app

description = 'Management of remote SODAR sites and remote project access'

Description string

entry_point_url_id = 'projectroles:remote_sites'

Entry point URL ID

icon = 'cloud'

FontAwesome icon ID string

name = 'remotesites'

Name (slug-safe, used in URLs)

title = 'Remote Site Access'

Title (used in templates)

urls = []

App URLs (will be included in settings by.djangoplugins)

class projectroles.plugins.**SiteAppPluginPoint**

Projectroles plugin point for registering site-wide apps

get_messages (*user=None*)

Return a list of messages to be shown to users.

Parameters **user** – User object (optional)

Returns List of dicts or and empty list if no messages

projectroles.plugins.**change_plugin_status** (*name, status, plugin_type='app'*)

Change the status of a selected plugin in the database.

Parameters

- **name** – Plugin name (string)

- **status** – Status (int, see.djangoplugins)
- **plugin_type** – Type of plugin (“app”, “backend” or “site”)

Raise ValueError if plugin_type is invalid or plugin with name not found

`projectroles.plugins.get_active_plugins(plugin_type='project_app', custom_order=False)`
Return active plugins of a specific type.

Parameters

- **plugin_type** – “project_app”, “site_app” or “backend” (string)
- **custom_order** – Order by plugin_ordering for project apps (boolean)

Returns List or None

Raise ValueError if plugin_type is not recognized

`projectroles.plugins.get_app_plugin(plugin_name)`
Return active app plugin.

Parameters **plugin_name** – Plugin name (string)

Returns ProjectAppPlugin object or None if not found

`projectroles.plugins.get_backend_api(plugin_name, force=False, **kwargs)`
Return backend API object. NOTE: May raise an exception from plugin.get_api().

Parameters

- **plugin_name** – Plugin name (string)
- **force** – Return plugin regardless of status in ENABLED_BACKEND_PLUGINS
- **kwargs** – Optional kwargs for API

Returns Plugin object or None if not found

4.6.2 Models

Projectroles models are used by other apps for project access and metadata management as well as linking objects to projects.

class `projectroles.models.AppSetting(*args, **kwargs)`
Project and users settings value.

The settings are defined in the “app_settings” member in a SODAR project app’s plugin. The scope of each setting can be either “USER” or “PROJECT”, defined for each setting in app_settings. Project AND user-specific settings or settings which don’t belong to either are currently not supported.

exception `DoesNotExist`

exception `MultipleObjectsReturned`

app_plugin

App to which the setting belongs

get_value()

Return value of the setting in the format specified in ‘type’

name

Name of the setting

project

Project to which the setting belongs

```

save (*args, **kwargs)
    Version of save() to convert 'value' data according to 'type'

sodar_uuid
    AppSetting SODAR UUID

type
    Type of the setting

user
    Project to which the setting belongs

user_modifiable
    Setting visibility in forms

value
    Value of the setting

value_json
    Optional JSON value for the setting

class projectroles.models.AppSettingManager
    Manager for custom table-level AppSetting queries

get_setting_value (app_name, setting_name, project=None, user=None)
    Return value of setting_name for app_name in project or for user.

    Note that project and/or user must be set.

    Parameters
    • app_name – App plugin name (string)
    • setting_name – Name of setting (string)
    • project – Project object or pk
    • user – User object or pk

    Returns Value (string)

    Raise AppSetting.DoesNotExist if setting is not found

class projectroles.models.Project (*args, **kwargs)
    A SODAR project. Can have one parent category in case of nested projects. The project must be of a specific
    type, of which "CATEGORY" and "PROJECT" are currently implemented. "CATEGORY" projects are used as
    containers for other projects

    exception DoesNotExist

    exception MultipleObjectsReturned

    description
    Short project description

    get_children ()
    Return child objects for the Project sorted by title

    get_delegates ()
    Return RoleAssignments for delegates

    get_depth ()
    Return depth of project in the project tree structure (root=0)

    get_full_title ()
    Return full title of project (just an alias for __str__())

```

get_members()
Return RoleAssignments for members of project excluding owner and delegates

get_owner()
Return RoleAssignment for owner or None if not set

get_parents()
Return an array of parent projects in inheritance order

get_source_site()
Return source site or None if this is a locally defined project

has_role(*user*, *include_children=False*)
Return whether user has roles in Project. If *include_children* is True, return True if user has roles in ANY child project

is_remote()
Return True if current project has been retrieved from a remote SODAR site

is_revoked()
Return True if remote access has been revoked for the project

parent
Parent category if nested, otherwise null

readme
Project README (optional, supports markdown)

save(*args, **kwargs)
Version of save() to include custom validation for Project

sodar_uuid
Project SODAR UUID

submit_status
Status of project creation

title
Project title

type
Type of project ("CATEGORY", "PROJECT")

class projectroles.models.ProjectInvite(*args, **kwargs)
Invite which is sent to a non-logged in user, determining their role in the project.

exception DoesNotExist

exception MultipleObjectsReturned

active
Status of the invite (False if claimed or revoked)

date_created
DateTime of invite creation

date_expire
Expiration of invite as DateTime

email
Email address of the person to be invited

issuer
User who issued the invite

```

message
    Message to be included in the invite email (optional)

project
    Project to which the person is invited

role
    Role assigned to the person

secret
    Secret token provided to user with the invite

sodar_uuid
    ProjectInvite SODAR UUID

class projectroles.models.ProjectManager
    Manager for custom table-level Project queries

    find (search_term, keywords=None, project_type=None)
        Return projects with a partial match in full title or, including titles of parent Project objects, or the description of the current object. Restrict to project type if project_type is set. :param search_term: Search term (string) :param keywords: Optional search keywords as key/value pairs (dict) :param project_type: Project type or None :return: List of Project objects

class projectroles.models.ProjectUserTag (*args, **kwargs)
    Tag assigned by a user to a project

    exception DoesNotExist

    exception MultipleObjectsReturned

    name
        Name of tag to be assigned

    project
        Project to which the tag is assigned

    sodar_uuid
        ProjectUserTag SODAR UUID

    user
        User for whom the tag is assigned

class projectroles.models.RemoteProject (*args, **kwargs)
    Remote project relation

    exception DoesNotExist

    exception MultipleObjectsReturned

    date_access
        DateTime of last access from/to remote site

    get_project ()
        Get the related Project object

    level
        Project access level

    project
        Related project object (if created locally)

    project_uuid
        Related project UUID

```

```
site
    Related remote SODAR site

sodar_uuid
    RemoteProject relation UUID (local)

class projectroles.models.RemoteSite (*args, **kwargs)
    Remote SODAR site

exception DoesNotExist

exception MultipleObjectsReturned

description
    Site description

get_access_date ()
    Return date of latest project access by remote site

get_url ()
    Return sanitized site URL

mode
    Site mode

name
    Site name

save (*args, **kwargs)
    Version of save() to include custom validation

secret
    Secret token used to connect to the master site

sodar_uuid
    RemoteSite relation UUID (local)

url
    Site URL

user_display
    RemoteSite's link visibilty for users

class projectroles.models.Role (*args, **kwargs)
    Role definition, used to assign roles to projects in RoleAssignment

exception DoesNotExist

exception MultipleObjectsReturned

description
    Role description

name
    Name of role

class projectroles.models.RoleAssignment (*args, **kwargs)
    Assignment of an user to a role in a project. One role per user is allowed for each project. Roles of project owner
    and project delegate assignments might be limited (to PROJECTROLES_DELEGATE_LIMIT) per project.

exception DoesNotExist

exception MultipleObjectsReturned
```



```

project
    Project in which role is assigned

role
    Role to be assigned

save (*args, **kwargs)
    Version of save() to include custom validation for RoleAssignment

sodar_uuid
    RoleAssignment SODAR UUID

user
    User for whom role is assigned

class projectroles.models.RoleAssignmentManager
    Manager for custom table-level RoleAssignment queries

    get_assignment (user, project)
        Return assignment of user to project, or None if not found

class projectroles.models.SODARUser (*args, **kwargs)
    SODAR compatible abstract user model

    get_full_name ()
        Return full name or username if not set

    sodar_uuid
        User SODAR UUID

projectroles.models.assign_user_group (sender, user, **kwargs)
    Signal for user group assignment

projectroles.models.handle_ldap_login (sender, user, **kwargs)
    Signal for LDAP login handling

```

4.6.3 App Settings

Projectroles provides an API for getting or setting project and user specific settings.

```

class projectroles.app_settings.AppSettingAPI

    classmethod get_all_defaults (scope, post_safe=False)
        Get all default settings for a scope.

        Parameters
        • scope – Setting scope (PROJECT, USER or PROJECT_USER)
        • post_safe – Whether POST safe values should be returned (bool)

        Returns Dict

    classmethod get_all_settings (project=None, user=None, post_safe=False)
        Return all setting values. If the value is not found, return the default.

        Parameters
        • project – Project object (can be None)
        • user – User object (can be None)
        • post_safe – Whether POST safe values should be returned (bool)

```

Returns Dict

Raise ValueError if neither project nor user are set

```
classmethod get_app_setting (app_name, setting_name, project=None, user=None,  
                             post_safe=False)
```

Return app setting value for a project or an user. If not set, return default.

Parameters

- **app_name** – App name (string, must correspond to “name” in app plugin)
- **setting_name** – Setting name (string)
- **project** – Project object (can be None)
- **user** – User object (can be None)
- **post_safe** – Whether a POST safe value should be returned (bool)

Returns String or None

Raise KeyError if nothing is found with setting_name

```
classmethod get_default_setting (app_name, setting_name, post_safe=False)
```

Get default setting value from an app plugin.

Parameters

- **app_name** – App name (string, must correspond to “name” in app plugin)
- **setting_name** – Setting name (string)
- **post_safe** – Whether a POST safe value should be returned (bool)

Returns Setting value (string, integer or boolean)

Raise KeyError if nothing is found with setting_name

```
classmethod get_setting_def (name, plugin=None, app_name=None)
```

Return definition for a single app setting, either based on an app name or the plugin object.

Parameters

- **name** – Setting name
- **plugin** – Plugin object extending ProjectAppPluginPoint
- **app_name** – Name of the app plugin (string)

Returns Dict

Raise ValueError if neither app_name or plugin are set or if setting is not found in plugin

```
classmethod get_setting_defs (scope, plugin=False, app_name=False,  
                             user_modifiable=False)
```

Return app setting definitions of a specific scope from a plugin.

Parameters

- **scope** – PROJECT, USER or PROJECT_USER
- **plugin** – project app plugin object extending ProjectAppPluginPoint
- **app_name** – Name of the app plugin (string)
- **user_modifiable** – Only return modifiable settings if True (boolean)

Returns Dict

Raise ValueError if scope is invalid or if neither app_name or plugin are set

classmethod set_app_setting (*app_name, setting_name, value, project=None, user=None, validate=True*)

Set value of an existing project or user settings. Creates the object if not found.

Parameters

- **app_name** – App name (string, must correspond to “name” in app plugin)
- **setting_name** – Setting name (string)
- **value** – Value to be set
- **project** – Project object (can be None)
- **user** – User object (can be None)
- **validate** – Validate value (bool, default=True)

Returns True if changed, False if not changed

Raise ValueError if validating and value is not accepted for setting type

Raise ValueError if neither project nor user are set

Raise KeyError if setting name is not found in plugin specification

classmethod validate_setting (*setting_type, setting_value*)

Validate setting value according to its type.

Parameters

- **setting_type** – Setting type
- **setting_value** – Setting value

Raise ValueError if setting_type or setting_value is invalid

4.6.4 Common Template Tags

These tags can be included in templates with `{% load 'projectroles_common_tags' %}`.

Template tags provided by projectroles for use in other apps

`projectroles.template_tags.projectroles_common_tags.check_backend(name)`

Return True if backend app is available, else False

`projectroles.template_tags.projectroles_common_tags.core_version()`

Return the SODAR Core version

`projectroles.template_tags.projectroles_common_tags.force_wrap(s, length)`

Force wrapping of string

`projectroles.template_tags.projectroles_common_tags.get_app_setting(app_name, setting_name, project=None, user=None)`

Get a project/user specific app setting from AppSettingAPI

`projectroles.template_tags.projectroles_common_tags.get_backend_include(backend_name, include_type='js')`

Returns import string for backend app Javascript or CSS. Returns empty string if not found.

`projectroles.templatetags.projectroles_common_tags.get_class(obj, lower=False)`

Return object class as string

`projectroles.templatetags.projectroles_common_tags.get_display_name(key, title=False, count=1, plural=False)`

Return display name from SODAR_CONSTANTS

`projectroles.templatetags.projectroles_common_tags.get_django_setting(name, default=None, js=False)`

Return value of Django setting by name or the default value if the setting is not found. Return a Javascript-safe value if js=True.

`projectroles.templatetags.projectroles_common_tags.get_full_url(request, url)`

Get full URL based on a local URL

`projectroles.templatetags.projectroles_common_tags.get_history_dropdown(project, obj)`

Return link to object timeline events within project

`projectroles.templatetags.projectroles_common_tags.get_info_link(content, html=False)`

Return info popover link icon

`projectroles.templatetags.projectroles_common_tags.get_project_by_uuid(sodar_uuid)`

Return Project by sodar_uuid

`projectroles.templatetags.projectroles_common_tags.get_project_link(project, full_title=False, request=None)`

Return link to project with a simple or full title

`projectroles.templatetags.projectroles_common_tags.get_project_title_html(project)`

Return HTML version of the full project title including parents

`projectroles.templatetags.projectroles_common_tags.get_remote_icon(project, request)`

Get remote project icon HTML

`projectroles.templatetags.projectroles_common_tags.get_user_by_username(username)`

Return User by username

`projectroles.templatetags.projectroles_common_tags.get_user_html(user)`

Return standard HTML representation for a User object

`projectroles.templatetags.projectroles_common_tags.get_visible_projects(projects, can_view_hidden_projects=)`

Return all projects that are either visible by user display or by view hidden permission

`projectroles.templatetags.projectroles_common_tags.highlight_search_term(item, term)`

Return string with search term highlighted

`projectroles.templatetags.projectroles_common_tags.render_markdown(raw_markdown)`

Markdown field rendering helper

`projectroles.templatetags.projectroles_common_tags.site_version()`

Return the site version

`projectroles.templatetags.projectroles_common_tags.static_file_exists(path)`

Return True/False based on whether a static file exists

`projectroles.templatetags.projectroles_common_tags.template_exists(path)`

Return True/False based on whether a template exists

4.6.5 Utilities

General utility functions are stored in `utils.py`.

`projectroles.utils.build_invite_url(invite, request)`

Return invite URL for a project invitation.

Parameters

- **invite** – ProjectInvite object
- **request** – HTTP request

Returns URL (string)

`projectroles.utils.build_secret(length=32)`

Return secret string for e.g. public URLs.

Parameters **length** – Length of string if specified, default value from settings

Returns Randomized secret (string)

`projectroles.utils.get_app_names()`

Return list of names for locally installed non-django apps

`projectroles.utils.get_display_name(key, title=False, count=1, plural=False)`

Return display name from SODAR_CONSTANTS.

Parameters

- **key** – Key in SODAR_CONSTANTS['DISPLAY_NAMES'] to return (string)
- **title** – Return name in title case if true (boolean, optional)
- **count** – Item count for returning plural form, overrides plural=False if not 1 (int, optional)
- **plural** – Return plural form if True, overrides count != 1 if True (boolean, optional)

Returns String

`projectroles.utils.get_expiry_date()`

Return expiry date based on current date + INVITE_EXPIRY_DAYS

Returns DateTime object

`projectroles.utils.get_user_display_name(user, inc_user=False)`

Return full name of user for displaying.

Parameters

- **user** – User object
- **inc_user** – Include user name if true (boolean)

Returns String

`projectroles.utils.set_user_group(user)`

Set user group based on user name.

ADMINALERTS APP

The `admindata` site app enables system administrators to display site-wide messages to all users with an expiration date.

5.1 Basics

The app displays un-dismissable small alerts on the top of page content to all users. They can be used to e.g. warn users of upcoming downtime or highlight recently deployed changes.

Upon creation, an expiration date is set for each alert. Alerts can also be freely enabled, disabled or deleted by superuser on the app UI. Additional information regarding an alert can be provided with Markdown syntax and viewed on a separate details page.

5.2 Installation

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

5.2.1 Django Settings

The `admindata` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'admindata.apps.AdminDataConfig',  
]
```

5.2.2 Optional Settings

To alter default `admindata` app settings, insert the following **optional** variables with values of your choosing:

```
# AdminData app settings  
ADMINDATA_PAGINATION = 15      # Number of alerts to be shown on one page (int)
```

5.2.3 URL Configuration

In the Django URL configuration file, add the following line under `urlpatterns` to include `adminalerts` URLs in your site.

```
urlpatterns = [  
    # ...  
    url(r'^alerts/', include('adminalerts.urls')),  
]
```

5.2.4 Migrate Database and Register Plugin

To migrate the Django database and register the `adminalerts` site app plugin, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for admimnalert.plugins.SiteAppPlugin
```

5.3 Usage

When logged in as a superuser, you can find the “Alerts” option in your user dropdown menu in the top right corner of the site. Using the UI, you can add, modify and delete alerts shown to users.

This application is not available for users with a non-superuser status.

BGJOBS APP

The `bgjobs` app allows for the management of project-specific and asynchronous server-side background jobs.

TODO: Docs to be filled out

6.1 Bgjobs Installation

This document provides instructions and guidelines for installing the `bgjobs` app to be used with your SODAR Core enabled Django site.

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

6.1.1 Django Settings

The `bgjobs` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'bgjobs.apps.BgjobsConfig',  
]
```

6.1.2 URL Configuration

In the Django URL configuration file, add the following line under `urlpatterns` to include `bgjobs` URLs in your site.

```
urlpatterns = [  
    # ...  
    url(r'^bgjobs/', include('bgjobs.urls')),  
]
```

6.1.3 Migrate Database and Register Plugin

To migrate the Django database and register the `bgjobs` app and job type plugins, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for bgjobs.plugins.ProjectAppPlugin  
Registering Plugin for bgjobs.plugins.BackgroundJobsPluginPoint
```

6.1.4 Celery Setup

TODO

6.2 Bgjobs Usage

Usage instructions for the `bgjobs` app are detailed in this document.

TODO

FILESFOLDERS APP

The `filesfolders` app enables uploading small files into the Django database and organizing them in folders. It also permits creating hyperlinks, providing public links to files and automated unpacking of ZIP archives.

The app is displayed as “*Small Files*” on the SODAR site.

7.1 Filesfolders Installation

This document provides instructions and guidelines for installing the `filesfolders` app to be used with your SODAR Core enabled Django site.

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

7.1.1 Django Settings

The `filesfolders` app is available for your Django site after installing `django-sodar-core`. Add the app, along with the prerequisite `django_db_storage` app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'filesfolders.apps.FilesfoldersConfig',  
    'db_file_storage',  
]
```

Next set the `db_file_storage` app as the default storage app for your site:

```
DEFAULT_FILE_STORAGE = 'db_file_storage.storage.DatabaseFileStorage'
```

Fill out `filesfolders` app settings to fit your site. The settings variables are explained below:

- `FILESFOLDERS_MAX_UPLOAD_SIZE`: Max size for an uploaded file in bytes (int)
- `FILESFOLDERS_MAX_ARCHIVE_SIZE`: Max size for an archive file to be unpacked in bytes (int)
- `FILESFOLDERS_SERVE_AS_ATTACHMENT`: If true, always serve downloaded files as attachment instead of opening them in browser (bool)
- `FILESFOLDERS_LINK_BAD_REQUEST_MSG`: Message to be displayed for a bad public link request (string)

Example of default values:

```
# Filesfolders app settings
FILESFOLDERS_MAX_UPLOAD_SIZE = env.int(
    'FILESFOLDERS_MAX_UPLOAD_SIZE', 10485760)
FILESFOLDERS_MAX_ARCHIVE_SIZE = env.int(
    'FILESFOLDERS_MAX_ARCHIVE_SIZE', 52428800)
FILESFOLDERS_SERVE_AS_ATTACHMENT = False
FILESFOLDERS_LINK_BAD_REQUEST_MSG = 'Invalid request'
```

7.1.2 URL Configuration

In the Django URL configuration file, add the following lines under `urlpatterns` to include filesfolders URLs in your site. The latter line is required by `db_file_storage` and should be obfuscated from actual users.

```
urlpatterns = [
    # ...
    url(r'^files/', include('filesfolders.urls')),
    url(r'^OBFUSCATED_STRING_HERE/', include('db_file_storage.urls')),
]
```

7.1.3 Migrate Database and Register Plugin

To migrate the Django database and register the filesfolders app plugin, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for filesfolders.plugins.ProjectAppPlugin
```

7.2 Filesfolders Usage

Usage instructions for the `filesfolders` app are detailed in this document.

7.2.1 Filesfolders UI


You can browse and manage files in the app's main view according to your permissions for each project. The “*File Operations*” menu is used to upload new files as well as add new folders or links. The menu also contains batch moving and deletion operations, for which items can be checked using the right hand side checkboxes.

Updating/deleting operations for single items can be accessed in the dropdown menus for each item. In the item create/update form, you can also *tag* items with a choice of icons and stylings to represent the item status.

When uploading a `.zip` archive, you may choose the “*Extract files from archive*” option to automatically extract archive files and folders into the filesfolders app. Note that overwriting of files is not currently allowed.

7.2.2 App Settings

In the project create/update form, set the boolean setting `filesfolders.allow_public_links` true to allow providing public links to files, for people who can access the site but do not necessarily have a user account or project rights. Note that public link access still has to be granted for each file through its create/update form.

 Small Files File Operations ▾

> root
















Name	Size	Description	Owner	Updated	
 test_folder		This is a subfolder	admin	2019-01-09 16:58	 <input type="checkbox"/>
 Web Link		This is a link	admin	2019-01-09 16:56	 <input type="checkbox"/>
 example.jpg 	69.1 KB	Example description	admin	2019-01-09 16:55	 <input type="checkbox"/>
 ms_powerpoint_xml.pptx	33.6 KB	Powerpoint test	admin	2019-01-09 16:56	 <input type="checkbox"/>
 report1.pdf 	7.8 KB	Publicly available file	admin	2019-01-09 16:58	 <input type="checkbox"/>
 test_basic.zip 	72.2 KB	Test archive	admin	2019-01-09 16:58	 <input type="checkbox"/>

Fig. 1: Filesfolders main view

USERPROFILE APP

The `userprofile` app is a site app which provides a user profile view for projectroles-compatible Django users and management of user specific settings.

8.1 Installation

It is **strongly recommended** to install the `userprofile` app into your site when using `projectroles`, unless you require a specific user profile providing app of your own.

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

8.1.1 Django Settings

The `userprofile` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'userprofile.apps.UserprofileConfig',  
]
```

8.1.2 URL Configuration

In the Django URL configuration file, add the following line under `urlpatterns` to include `userprofile` URLs in your site.

```
urlpatterns = [  
    # ...  
    url(r'^user/', include('userprofile.urls')),  
]
```

8.1.3 Register Plugin

To register the app plugin, run the following management command:

```
$ ./manage.py syncplugins
```

You should see the following output:

```
Registering Plugin for userprofile.plugins.ProjectAppPlugin
```

8.2 Usage

After successful installation, the link for “User Profile” should be available in the user dropdown menu in the top-right corner of the website UI after you have logged in.

8.3 User Settings

User settings are configured in the `app_settings` dictionary in your project app plugins.

SITEINFO APP

The `siteinfo` site app enables system administrators and developers to view site details and statistics gathered from project and backend apps.

9.1 Basics

The app renders a site which displays information and statistics regarding the site and installed SODAR apps. Providing app statistics for `siteinfo` done via implementing the `get_statistics()` function in your app plugins. Currently, access to the app is limited to site administrators.

9.2 Installation

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

9.2.1 Django Settings

The `siteinfo` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [
    # ...
    'siteinfo.apps.SiteinfoConfig',
]
```

9.2.2 URL Configuration

In the Django URL configuration file, add the following line under `urlpatterns` to include `siteinfo` URLs in your site.

```
urlpatterns = [
    # ...
    url(r'^siteinfo/', include('siteinfo.urls')),
]
```

9.2.3 Migrate Database and Register Plugin

To migrate the Django database and register the siteinfo site app plugin, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for siteinfo.plugins.SiteAppPlugin
```

9.3 Usage

When logged in as a superuser, you can find the “Site Info” link in your user dropdown menu in the top right corner of the site.

This application is not available for users with a non-superuser status.

9.3.1 Providing App Statistics

In your project app or backend plugin, implement the `get_statistics()` function. It should return a dictionary containing, for each statistics item, a program friendly key and certain member fields:

- `label`: Human readable label for the statistics item.
- `value`: The value to be rendered
- `url`: The url to link to from the value for additional information (optional)
- `description`: Additional information (optional)

Example:

```
def get_statistics(self):
    return {
        'stat_id': {
            'label': 'Some statistic',
            'value': 9000,
            'url': reverse('home'),
            'description': 'More information here'
        }
    }
```

SODARCACHE APP

The `sodarcache` app provides a generic data caching functionality for a SODAR Core based site. This can be used to e.g. locally cache and aggregate data referring to external sources in order to speed up commonly repeated queries to databases other than the local Django PostgreSQL.

10.1 Sodarcache Installation

This document provides instructions and guidelines for installing the `sodarcache` app to be used with your SODAR Core enabled Django site.

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

10.1.1 Django Settings

The `sodarcache` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'sodarcache.apps.SodarCacheConfig',  
]
```

You also need to add the `sodarcache` backend plugin in enabled backend plugins.

```
ENABLED_BACKEND_PLUGINS = [  
    # ...  
    'sodar_cache',  
]
```

10.1.2 URL Configuration

In the Django URL configuration file, add the following lines under `urlpatterns` to include `sodarcache` URLs in your site.

```
urlpatterns = [
    # ...
    url(r'^cache/', include('sodarcache.urls')),
]
```

10.1.3 Migrate Database and Register Plugin

To migrate the Django database and register the sodarcache app plugin, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for sodarcache.plugins.BackendPlugin
```

10.2 Sodar Cache Usage

Usage instructions for the `sodarcache` app are detailed in this document.

10.2.1 Backend API for Data Caching

The API for logging events is located in `sodarcache.api`. For the full API documentation, see [here](#).

Invoking the API

The API is accessed through a backend plugin. This means you can write calls to the API without any hard-coded imports and your code should work even if the sodarcache app has not been installed on the site.

Initialize the API using `projectroles.plugins.get_backend_api()` as follows:

```
from projectroles.plugins import get_backend_api
projectcache = get_backend_api('sodar_cache')

if projectcache:    # Only proceed if the backend was successfully initialized
    pass
```

Setting and getting Cache Items

Once you can access the sodarcache backend, you should set up the `update_cache()` function in the `ProjectAppPlugin` of the app with which you want to cache or aggregate data. The update process can be limited by two parameters: cached item name and project. If neither are specified, the function should update cached data for all known items within all projects.

```
def update_cache(self, name=None, project=None):
    """
    Update cached data for this app, limitable to item ID and/or project.

    :param project: Project object to limit update to (optional)
    :param name: Item name to limit update to (string, optional)
```

(continues on next page)

(continued from previous page)

```
"""
# TODO: Implement this in your app plugin
return None
```

Updating a specific cache item within the `update_cache()` function (or elsewhere) should be done using `sodarcache.api.set_cache_item()`. A minimal example is as follows:

```
cache_item = projectcache.set_cache_item(
    project=project,          # Project object
    app_name=APP_NAME,        # Name of the current app
    user=request.user,        # The user triggering the cache update
    name='some_item',         # Cached item ID
    data_type='json',         # Data type ("json" currently supported)
    data={'key': 'val'},      # The actual data that should be cached
)
```

Note: The item ID in the `name` argument is not unique, but it is expected to be unique together with the `project` and `app_name` arguments.

Retrieve items with `sodarcache.get_cache_item()` or just check the time the item was last updated with `sodarcache.get_update_time()` like this:

```
projectcache.get_cache_item(
    app_name='yourapp',
    name='some_item',
    project=project,
    data_type='json'
) # Returns a JsonCacheItem

projectcache.get_update_time(
    app_name='yourapp',
    name='some_item',
    project=project
)
```

It is also possible to retrieve a Queryset with all cached items for a specific project with `sodarcache.get_project_cache()`

```
projectcache.get_project_cache(
    project=project,          # Project object
    data_type='json'         # must be 'json' for JsonCacheItem
)
```

Using the Management commands

To create or update the data cache for all apps and projects, you can use a management command.

```
$ ./manage.py synccache
```

To limit the sync to a specific project, you can provide the `-p` or `--project` argument with the project UUID.

```
$ ./manage.py synccache -p e9701604-4ccc-426c-a67c-864c15aff6e2
```

Similarly, there is a command to delete all cached data:

```
$ ./manage.py deletecache
```

10.3 Sodarcache Backend API Documentation

This document contains API documentation for the backend plugin in the `sodarcache` app. Included are functionalities and classes intended to be used by other applications.

10.3.1 Backend API

The `SodaCacheAPI` class contains the Soda Cache backend API. It should be initialized with `Projectroles.plugins.get_backend_api('sodar_cache')`.

class `sodarcache.api.SodaCacheAPI`

SodaCache backend API to be used by Django apps.

classmethod `delete_cache` (*app_name=None, project=None*)

Delete cache items. Optionallly limit to project and/or user.

Parameters

- **app_name** – Name of the app which sets the item (string)
- **project** – Project object (optional)

Returns Integer (deleted item count)

Raise `ValueError` if `app_name` is given but invalid

classmethod `get_cache_item` (*app_name, name, project=None*)

Return cached data by `app_name`, `name` (identifier) and optional project. Returns `None` if not found.

Parameters

- **name** – Item name (string)
- **app_name** – Name of the app which sets the item (string)
- **project** – Project object (optional)

Returns `JSONCacheItem` object

Raise `ValueError` if `app_name` is invalid

classmethod `get_project_cache` (*project, data_type='json'*)

Return all cached data for a project.

Parameters

- **project** – Project object
- **data_type** – String stating the data type of the cache items

Returns `QuerySet`

Raise `ValueError` if `data_type` is invalid

classmethod `get_update_time` (*app_name, name, project=None*)

Return the time of the last update of a cache object as seconds since epoch.

Parameters

- **name** – Item name (string)

- **app_name** – Name of the app which sets the item (string)
- **project** – Project object (optional)

Returns Float

classmethod set_cache_item (*app_name, name, data, data_type='json', project=None, user=None*)

Create or update and save a cache item.

Parameters

- **app_name** – Name of the app which sets the item (string)
- **name** – Item name (string)
- **data** – Item data (dict)
- **data_type** – String stating the data type of the cache items
- **project** – Project object (optional)
- **user** – User object to denote user triggering the update (optional)

Returns JSONCacheItem object

Raise ValueError if app_name is invalid

Raise ValueError if data_type is invalid

classmethod update_cache (*name=None, project=None, user=None*)

Update items by certain name within a project by calling implemented functions in project app plugins.

Parameters

- **name** – Item name to limit update to (string, optional)
- **project** – Project object to limit update to (optional)
- **user** – User object to denote user triggering the update (optional)

10.3.2 Models

class sodarcache.models.**BaseCacheItem** (**args, **kwargs*)

Abstract class representing a cached item

app_name

App name

date_modified

DateTime of the update

name

Identifier for the item given by the data setting app

project

Project in which the item belongs (optional)

sodar_uuid

UUID for the item

user

User who updated the item (optional)

class sodarcache.models.**JSONCacheItem** (**args, **kwargs*)

Class representing a cached item in JSON format

`exception DoesNotExist`

`exception MultipleObjectsReturned`

`data`

 Cached data as JSON

TASKFLOW BACKEND

The `taskflowbackend` backend app is an optional add-on used if your site setup contains the separate **SODAR Taskflow** data transaction service.

If you have not set up a SODAR Taskflow service for any purpose, this backend is not needed and can be ignored.

11.1 Basics

The `taskflowbackend` backend app is used in the main SODAR site to communicate with an external SODAR Taskflow service to manage large-scale data transactions. It has no views or database models and only provides an API for other apps to use.

Note: At the time of writing, SODAR Taskflow is in development and has not been made public.

11.2 Installation

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

11.2.1 Django Settings

The `taskflowbackend` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [
    # ...
    'taskflowbackend.apps.TaskflowbackendConfig',
]
```

Next add the backend to the list of enabled backend plugins:

```
ENABLED_BACKEND_PLUGINS = env.list('ENABLED_BACKEND_PLUGINS', None, [
    # ...
    'taskflow',
])
```

The following app settings **must** be included in order to use the backend. Note that the values for TASKFLOW_TARGETS depend on your SODAR Taskflow configuration.

```
# Taskflow backend settings
TASKFLOW_BACKEND_HOST = env.str('TASKFLOW_BACKEND_HOST', 'http://0.0.0.0')
TASKFLOW_BACKEND_PORT = env.int('TASKFLOW_BACKEND_PORT', 5005)
TASKFLOW_SODAR_SECRET = env.str('TASKFLOW_SODAR_SECRET', 'CHANGE ME!')
TASKFLOW_TARGETS = [
    'sodar',
    # ..
]
```

11.2.2 Register Plugin

To register the taskflowbackend plugin, run the following management command:

```
$ ./manage.py syncplugins
```

You should see the following output:

```
Registering Plugin for taskflowbackend.plugins.BackendPlugin
```

11.3 Usage

Once enabled, Retrieve the backend API class with the following in your Django app python code:

```
from projectroles.plugins import get_backend_api
taskflow = get_backend_api('taskflow')
```

See the docstrings of the API for more details.

To initiate sync of existing data with your SODAR Taskflow service, you can use the following management command:

```
./manage.py synctaskflow
```

11.4 API Documentation

The TaskflowAPI class contains the SODAR Taskflow backend API. It should be initialized using the Projectroles.plugins.get_backend_api() function.

```
class taskflowbackend.api.TaskflowAPI
    SODAR Taskflow API to be used by Django apps

    exception CleanupException
        SODAR Taskflow cleanup exception

    exception FlowSubmitException
        SODAR Taskflow submission exception

    cleanup()
        Send a cleanup command to SODAR Taskflow. Only allowed in test mode.

        Returns Boolean
```

Raise ImproperlyConfigured if TASKFLOW_TEST_MODE is not set True

Raise CleanupException if SODAR Taskflow raises an error

get_error_msg (*flow_name, submit_info*)

Return a printable version of a SODAR Taskflow error message.

Parameters

- **flow_name** – Name of submitted flow
- **submit_info** – Returned information from SODAR Taskflow

Returns String

submit (*project_uuid, flow_name, flow_data, request=None, targets=['sodar'], request_mode='sync', timeline_uuid=None, force_fail=False, sodar_url=None*)

Submit taskflow for SODAR project data modification.

Parameters

- **project_uuid** – UUID of the project (UUID object or string)
- **flow_name** – Name of flow to be executed (string)
- **flow_data** – Input data for flow execution (dict)
- **request** – Request object (optional)
- **targets** – Names of backends to sync with (list)
- **request_mode** – “sync” or “async”
- **timeline_uuid** – UUID of corresponding timeline event (optional)
- **force_fail** – Make flow fail on purpose (boolean, default False)
- **sodar_url** – URL of SODAR server (optional, for testing)

Returns Boolean

Raise FlowSubmitException if submission fails

use_taskflow (*project*)

Check whether taskflow use is allowed with a project.

Parameters **project** – Project object

Returns Boolean

TIMELINE APP

The `timeline` app enables the developer of a SODAR Core based site to log project related user events and link objects (both existing and deleted) to those events.

Unlike the standard Django object history accessible in the admin site, these events are not restricted to creation/modification of objects in the Django database, but can concern any user-triggered activity.

The events can also have multiple temporal status states in case of e.g. events requiring async requests.

The app provides front-end views to list project timeline events, as well as a backend API for saving desired activity as timeline events. For details on how to use these, see the [timeline usage documentation](#).

12.1 Timeline Installation

This document provides instructions and guidelines for installing the `timeline` app to be used with your SODAR Core enabled Django site.

Warning: To install this app you **must** have the `django-sodar-core` package installed and the `projectroles` app integrated into your Django site. See the [projectroles integration document](#) for instructions.

12.1.1 Django Settings

The `timeline` app is available for your Django site after installing `django-sodar-core`. Add the app into `THIRD_PARTY_APPS` as follows:

```
THIRD_PARTY_APPS = [  
    # ...  
    'timeline.apps.TimelineConfig',  
]
```

You also need to add the `timeline` backend plugin in enabled backend plugins.

```
ENABLED_BACKEND_PLUGINS = [  
    # ...  
    'timeline_backend',  
]
```

12.1.2 Optional Settings

To alter default timeline app settings, insert the following **optional** variables with values of your choosing:

```
# Timeline app settings
TIMELINE_PAGINATION = 15      # Number of events to be shown on one page (int)
```

12.1.3 URL Configuration

In the Django URL configuration file, add the following line under `urlpatterns` to include timeline URLs in your site.

```
urlpatterns = [
    # ...
    url(r'^timeline/', include('timeline.urls')),
]
```

12.1.4 Migrate Database and Register Plugin

To migrate the Django database and register the timeline app/backend plugins, run the following management command:

```
$ ./manage.py migrate
```

In addition to the database migration operation, you should see the following output:

```
Registering Plugin for timeline.plugins.ProjectAppPlugin
Registering Plugin for timeline.plugins.BackendPlugin
```

12.2 Timeline Usage

Usage instructions for the `timeline` app are detailed in this document.

12.2.1 Timeline UI

You can browse events logged for each project by navigating to the project and selecting the “Timeline” app from the project sidebar.

By clicking on the time stamp for each event, you can see details of the event execution (in case of e.g. asynchronous events).

By clicking on the clock icon next to an object link in the event description, you can view the event history of that object. The link itself will take you to the relevant view for the object on your Django site.

Certain events have a file icon in their description. If clicked, a popup showing a collection of extra data for the given event will appear. It will show the extra data of the event itself and of the different states the event went through, if there are any.

Admin users are able to see certain “*classified*” level events hidden from normal users.

🕒 Project Timeline

Timestamp	App	Event	User	Description	Status
2019-01-09 16:58:27	filesfolders	folder_update	admin	update folder test_folder (description)	OK
2019-01-09 16:58:12	filesfolders	file_update	admin	update file test_basic.zip (flag)	OK
2019-01-09 16:58:01	filesfolders	file_create	admin	create file report1.pdf	OK
2019-01-09 16:57:35	projectroles	project_update	admin	update project (settings.filesfolders.allow_public_links)	OK
2019-01-09 16:57:08	filesfolders	file_update	admin	update file test_basic.zip (description)	OK
2019-01-09 16:56:57	filesfolders	hyperlink_create	admin	create hyperlink Web Link	OK
2019-01-09 16:56:19	filesfolders	file_create	admin	create file ms_powerpoint_xml.pptx	OK
2019-01-09 16:56:04	filesfolders	file_create	admin	create file test_basic.zip	OK

Fig. 1: Timeline event list view

12.2.2 Backend API for Event Logging

The API for logging events is located in `timeline.api`. For the full API documentation, see [here](#).

Invoking the API

The API is accessed through a backend plugin. This means you can write calls to the API without any hard-coded imports and your code should work even if the timeline app has not been installed on the site.

The most common use case is to save events within the Class-Based Views of your Django site, but technically this can be done by any part of the code in your Django apps.

Initialize the API using `projectroles.plugins.get_backend_api()` as follows:

```
from projectroles.plugins import get_backend_api
timeline = get_backend_api('timeline_backend')

if timeline:      # Only proceed if the backend was successfully initialized
    pass          # Save your events here..
```

Adding an Event

Once you can access the timeline backend, add the event with `timeline.add_event()`. A minimal example is as follows:

```
tl_event = timeline.add_event(
    project=project,          # Project object
    app_name=APP_NAME,        # Name of the current app
    user=request.user,         # The user triggering the activity being saved
    event_name='some_event',   # You can define these yourself, not unique
    description='Description') # Human readable description
```

Linking an Object

Say you want to link a Django model object to the event for tracking its history? In this example, let's say it's a SODAR Core compatible `User` model object `user_obj`.

Note: The given object **must** contain an `sodar_uuid` field with an auto-generated UUID. For more information, see the [project app development document](#).

Create the event as in the previous section, but add a label `target_user` in the description. The name of the label is arbitrary:

```
tl_event = timeline.add_event(  
    project=project,  
    app_name=APP_NAME,  
    user=request.user,  
    event_name='some_event',  
    description='Do something to {target_user}')
```

All you have to do is add an object reference to the created event:

```
obj_ref = tl_event.add_object(  
    obj=user_obj,  
    label='target_user',  
    name=user_obj.username)
```

The `name` field specifies which name the object will be referred to when displaying the event description to a user.

Defining Object References

The example before is all fine and good for a `User` object, but what about your own custom Django model?

When encountering an unknown object model from your app, timeline will call the `get_object_link()` function in the `ProjectAppPlugin` defined for your app. Make sure to implement it for all the relevant models in your app.

Displaying Object Links

In order to display object links with timeline history link included, you can use the `timeline.api.get_object_link()` function in your app's template tags.

Defining Status States

Note: If your Django apps only deal with normal synchronous requests, you don't need to pay attention to this functionality right now.

By default, `timeline.add_event()` treats events as synchronous and automatically saves them with the status of `OK`. However, in case of e.g. asynchronous requests, you can alter this by setting the `status_type` and (optionally) `status_desc` types upon creation.


```
tl_event = timeline.add_event(
    project=project,
    app_name=APP_NAME,
    user=request.user,
    event_name='some_event',
    description='Description',
    status_type='SUBMIT',
    status_desc='Just submitted this')
```

After that, you can add new status states for the event using the object returned by `timeline.add_event()`:

```
tl_event.set_status('OK', 'Submission was successful!')
```

Currently supported status types are listed below, some only applicable to async events:

- OK: All OK, event successfully performed
- INFO: Used for events which do not change anything, e.g. viewing something within an app
- INIT: Initializing the event in progress
- SUBMIT: Event submitted asynchronously
- FAILED: Asynchronous event submission failed
- CANCEL: Event cancelled

Extra Data

Extra data can be added in the JSON format for both events and their status states with the `extra_data` and `status_extra_data` parameters.

Specifying a label `{extra-NAME}` in the event description will lead to a callback to `get_extra_data_link()` in the app plugin. To support this you need to make sure to implement the `get_extra_data_link()` function in your plugin.

Classified Events

To mark an event “*classified*”, that is, restricting its visibility to project owners and admins, set the `classified` argument to `true` when invoking `timeline.add_event()`.

Note: Multiple levels of classification may be introduced to the timeline event model in the future.

12.3 Timeline API Documentation

This document contains API documentation for the `timeline` app. Included are functionalities and classes intended to be used by other applications.

12.3.1 Backend API

The `TimelineAPI` class contains the Timeline backend API. It should be initialized using the `Projectroles.plugins.get_backend_api()` function.

class `timeline.api.TimelineAPI`

Timeline backend API to be used by Django apps.

static `add_event` (*project*, *app_name*, *user*, *event_name*, *description*, *classified=False*,
extra_data=None, *status_type=None*, *status_desc=None*, *status_extra_data=None*)

Create and save a timeline event.

Parameters

- **project** – Project object
- **app_name** – ID string of app from which event was invoked (NOTE: should correspond to member “name” in app plugin!)
- **user** – User invoking the event
- **event_name** – Event ID string (must match schema)
- **description** – Description of status change (may include {object label} references)
- **classified** – Whether event is classified (boolean, optional)
- **extra_data** – Additional event data (dict, optional)
- **status_type** – Initial status type (string, optional)
- **status_desc** – Initial status description (string, optional)
- **status_extra_data** – Extra data for initial status (dict, optional)

Returns ProjectEvent object

Raise ValueError if app_name or status_type is invalid

static `get_event_description` (*event*, *request=None*)

Return the description of a timeline event as HTML.

Parameters

- **event** – ProjectEvent object
- **request** – Request object (optional)

Returns String (contains HTML)

static `get_object_link` (*project_uuid*, *obj*)

Return an inline HTML icon link for a timeline event object history.

Parameters

- **project_uuid** – UUID of the related project
- **obj** – Django database object

Returns String (contains HTML)

static `get_object_url` (*project_uuid*, *obj*)

Return the URL for a timeline event object history.

Parameters

- **project_uuid** – UUID of the related project
- **obj** – Django database object

Returns String

static get_project_events (*project*, *classified=False*)

Return timeline events for a project.

Parameters

- **project** – Project object
- **classified** – Include classified (boolean)

Returns QuerySet

12.3.2 Models

class timeline.models.**ProjectEvent** (**args*, ***kwargs*)

Class representing a Project event

exception DoesNotExist

exception MultipleObjectsReturned

add_object (*obj*, *label*, *name*, *extra_data=None*)

Add object reference to an event.

Parameters

- **obj** – Django object to which we want to refer
- **label** – Label for the object in the event description (string)
- **name** – Name or title of the object (string)
- **extra_data** – Additional data related to object (dict, optional)

Returns ProjectEventObjectRef object

app

App from which the event was triggered

classified

Event is classified (only viewable by user levels specified in rules)

description

Description of status change (may include {object_name} references)

event_name

Event ID string

extra_data

Additional event data as JSON

get_current_status ()

Return the current event status

get_status_changes (*reverse=False*)

Return all status changes for the event

get_timestamp ()

Return the timestamp of current status

project

Project in which the event belongs

set_status (*status_type*, *status_desc=None*, *extra_data=None*)

Set event status.

Parameters

- **status_type** – Status type string (see EVENT_STATUS_TYPES)
- **status_desc** – Description string (optional)
- **extra_data** – Extra data for the status (dict, optional)

Returns ProjectEventStatus object

Raise TypeError if status_type is invalid

sodar_uuid

UUID for the event

user

User who initiated the event

class timeline.models.**ProjectEventManager**

Manager for custom table-level ProjectEvent queries

get_object_events (*project, object_model, object_uuid, order_by='pk'*)

Return events which are linked to an object reference.

Parameters

- **project** – Project object
- **object_model** – Object model (string)
- **object_uuid** – sodar_uuid of the original object
- **order_by** – Ordering (default = pk descending)

Returns QuerySet

class timeline.models.**ProjectEventObjectRef** (**args, **kwargs*)

Class representing a reference to an object (existing or removed) related to a Timeline event status

exception DoesNotExist

exception MultipleObjectsReturned

event

Event to which the object belongs

extra_data

Additional data related to the object as JSON

label

Label for the object related to the event

name

Name or title of the object

object_model

Object model as string

object_uuid

Object SODAR UUID

class timeline.models.**ProjectEventStatus** (**args, **kwargs*)

Class representing a Timeline event status

exception DoesNotExist

exception MultipleObjectsReturned

description

Description of status change (optional)

event

Event to which the status change belongs

extra_data

Additional status data as JSON

status_type

Type of the status change

timestamp

DateTime of the status change

DEVELOPMENT

This document presents instructions and guidelines for developing apps compatible with the SODAR Core framework, as well as development of the SODAR Core package itself.

13.1 General Development Topics

13.1.1 Guidelines

- Best practices from [Two Scoops](#) should be followed where applicable
- To maintain consistency, app packages should be named without delimiting characters, e.g. `projectroles` and `userprofile`
- It is recommended to add a “*Projectroles dependency*” comment when directly importing e.g. mixins or tags from the `projectroles` app
- **Hard-coded imports from apps *other than* `projectroles` should be avoided**
 - Use the plugin structure instead
 - See the `example_backend_app` for an example
- Using Bootstrap 4 classes together with SODAR specific overrides and extensions provided in `projectroles.js` is recommended

13.1.2 Common Helpers

Via the `projectroles` app, SODAR Core provides optional templates for aiding in maintaining common functionality and layout. Those are defined here.

App Setting API

For accessing and modifying app settings for project or site apps, you should use the `AppSettingAPI`. Below is an example of invoking the API. For the full API docs, see [Projectroles API Documentation](#).

```
from projectroles.app_settings import AppSettingAPI
app_settings = AppSettingAPI()
app_settings.get_app_setting('app_name', 'setting_name', project_object) # Etc..
```

Pagination Template

A common template for adding navigation for list pagination can be found in `projectroles/_pagination.html`. This can be included to any Django `ListView` template which provides the `paginate_by` definition, enabling pagination. If a smaller layout is desired, the `pg_small` argument can be used. An example can be seen below:

```
{% include 'projectroles/_pagination.html' with pg_small=True %}
```

13.2 Project App Development

This document details instructions and guidelines for developing **project apps** to be used with the SODAR Core framework. This also applies for modifying existing Django apps into project apps.

Hint: The package `example_project_app` in the `projectroles` repository provides a concrete minimal example of a working project app.

13.2.1 Project App Basics

Characteristics of a project app:

- Provides a functionality related to a project
- Is dynamically included in project views by `projectroles` using plugins
- Uses the project-based role and access control provided by `projectroles`
- Is included in `projectroles` search (optionally)
- Provides a dynamically included element (e.g. content overview) for the project details page
- Appears in the project menu sidebar in the default `projectroles` templates

Requirements for setting up a project app:

- Implement project relations and SODAR UUIDs in the app's Django models
- Use provided mixins, keyword arguments and conventions in views
- Extend `projectroles` base templates in your templates
- Implement specific templates for dynamic inclusion by `Projectroles`
- Implement `plugins.py` with definitions and function implementations
- Implement `rules.py` with access rules

Fulfilling these requirements is detailed further in this document.

13.2.2 Prerequisites

This documentation assumes you have a Django project with the `projectroles` app set up (see the [projectroles integration document](#)). The instructions can be applied either to modify a previously existing app, or to set up a fresh app generated in the standard way with `./manage.py startapp`.

It is also assumed that apps are more or less created according to best practices defined by [Two Scoops](#), with the use of [Class-Based Views](#) being a requirement.

13.2.3 Models

In order to hook up your Django models into projects, there are two requirements: implementing a **project foreign key** and a **UUID field**.

Project Foreign Key

Add a `ForeignKey` field for the `projectroles.models.Project` model, either called `project` or accessible with a `get_project()` function implemented in your model.

If the project foreign key for your is **not** `project`, make sure to define a `get_project_filter_key()` function. It should return the name of the field to use as key for filtering your model by project.

Note: If your app contains a complex model structure with e.g. nested models using foreign keys, it's not necessary to add this to all your models, just the topmost one(s) used e.g. in URL kwargs.

Model UUID Field

To provide a unique identifier for objects in the SODAR context, add a `UUIDField` with the name of `sodar_uuid` into your model.

Note: Projectroles links to objects in URLs, links and forms using UUIDs instead of database private keys. This is strongly recommended for all Django models in apps using the projectroles framework.

Note: When updating an existing Django model with an existing database, the `sodar_uuid` field needs to be populated. See [instructions in Django documentation](#) on how to create the required migrations.

Model Example

Below is an example of a projectroles-compatible Django model:

```
import uuid
from django.db import models
from projectroles.models import Project

class SomeModel(models.Model):
    some_field = models.CharField(
        help_text='Your own field'
    )
    project = models.ForeignKey(
        Project,
        related_name='some_objects',
        help_text='Project in which this object belongs',
    )
```

(continues on next page)

(continued from previous page)

```
sodar_uuid = models.UUIDField(  
    default=uuid.uuid4,  
    unique=True,  
    help_text='SomeModel SODAR UUID',  
)
```

Note: The `related_name` field is optional, but recommended as it provides an easy way to lookup objects of a certain type related to a project. For example the `project` foreign key in a model called `Document` could feature e.g. `related_name='documents'`.

13.2.4 Rules File

Create a file `rules.py` in your app's directory. You should declare at least one basic rule for enabling a user to view the app data for the project. This can be named e.g. `{APP_NAME}.view_data`. Predicates for the rules can be found in `projectroles` and they can be extended within your app if needed.

```
import rules  
from projectroles import rules as pr_rules  
  
rules.add_perm(  
    'example_project_app.view_data',  
    pr_rules.is_project_owner  
    | pr_rules.is_project_delegate  
    | pr_rules.is_project_contributor  
    | pr_rules.is_project_guest,  
)
```

Hint: The `rules.is_superuser` predicate is often redundant, as permission checks are skipped for Django superusers. However, it can be handy if you e.g. want to define a rule allowing only superuser access for now, with the potential for adding other predicates later.

13.2.5 ProjectAppPlugin

Create a file `plugins.py` in your app's directory. In the file, declare a `ProjectAppPlugin` class implementing `projectroles.plugins.ProjectAppPluginPoint`. Within the class, implement member variables and functions as instructed in comments and docstrings.

```
from projectroles.plugins import ProjectAppPluginPoint  
from .urls import urlpatterns  
  
class ProjectAppPlugin(ProjectAppPluginPoint):  
    """Plugin for registering app with Projectroles"""  
    name = 'example_project_app'  
    title = 'Example Project App'  
    urls = urlpatterns  
    # ...
```

The following variables and functions are **mandatory**:

- `name`: App name (**NOTE**: should correspond to the app package name or some functionality may not work as expected)
- `title`: Printable app title
- `urls`: Urlpatterns (usually imported from the app's `urls.py` file)
- `icon`: Font Awesome 4.7 icon name (without the `fa-*` prefix)
- `entry_point_url_id`: View ID for the app entry point (**NOTE**: The view **must** take the project `sodar_uuid` as a kwarg named `project`)
- `description`: Verbose description of app
- `app_permission`: Basic permission for viewing app data in project (see above)
- `search_enable`: Boolean for enabling/disabling app search
- `details_template`: Path to template to be included in the project details page, usually called `{APP_NAME}/_details_card.html`
- `details_title`: Title string to be displayed in the project details page for the app details template
- `plugin_ordering`: Number to define the ordering of the app on the project menu sidebar and the details page

Implementing the following is **optional**:

- `app_settings`: Implement if project, user or project_user (Settings specific to a project and user) specific settings for the app are needed. See the plugin point definition for an example.
- `search_types`: Implement if searching the data of the app is enabled
- `search_template`: Implement if searching the data of the app is enabled
- `project_list_columns`: Optional custom columns do be shown in the project list. See the plugin point definition for an example.
- `get_taskflow_sync_data()`: Applicable only if working with `sodar_taskflow` and `iRODS`
- `get_object_link()`: If Django models are associated with the app. Used e.g. by `django-sodar-timeline`.
- `search()`: Function called when searching for data related to the app if search is enabled
- `get_statistics()`: Return statistics for the siteinfo app. See details in [the siteinfo documentation](#).
- `get_project_list_value()`: A function which **must** be implemented if `project_list_columns` are defined, to retrieve a column cell value for a specific project.

Once you have implemented the `rules.py` and `plugins.py` files and added the app and its URL patterns to the Django site configuration, you can create the project app plugin in the Django database with the following command:

```
$ ./manage.py syncplugins
```

You should see the following output to ensure the plugin was successfully registered:

```
Registering Plugin for {APP_NAME}.plugins.ProjectAppPlugin
```

For info on how to implement the specific required views/templates, see the end of this document.

13.2.6 Views

Certain guidelines must be followed in developing Django web UI views for them to be successfully used with `projectroles`.

URL Keyword Arguments

In order to link a view to project and check user permissions using mixins, the URL keyword arguments **must** include an argument which matches *one of the following conditions*:

- Contains a kwarg `project` which corresponds to the `sodar_uuid` member value of a `projectroles.models.Project` object
- Contains a kwarg corresponding to the `sodar_uuid` of another Django model, which must contain a member field `project` which is a foreign key for a `Projectroles.models.Project` object. The kwarg **must** be named after the Django model of the referred object (in lowercase).
- Same as above, but the Django model provides a `get_project()` function which returns (you guessed it) a `Projectroles.models.Project` object.

Examples:

```
urlpatterns = [  
    # Direct reference to the Project model  
    url(  
        regex=r'^(?P<project>[0-9a-f-]+)$',  
        view=views.ProjectDetailView.as_view(),  
        name='detail',  
    ),  
    # RoleAssignment model has a "project" member which is also OK  
    url(  
        regex=r'^members/update/(?P<roleassignment>[0-9a-f-]+)$',  
        view=views.RoleAssignmentUpdateView.as_view(),  
        name='role_update',  
    ),  
]
```

Mixins

The `projectroles.views` module provides several useful mixins for augmenting your view classes to add `projectroles` functionality. These can be found in the `projectroles.views` module.

The most commonly used mixins:

- `LoggedInPermissionMixin`: Ensure correct redirection of users on no permissions
- `ProjectPermissionMixin`: Provides a `Project` object for permission checking based on URL kwargs
- `ProjectContextMixin`: Provides a `Project` object into the view context based on URL kwargs

See `example_project_app.views.ExampleView` for an example.

13.2.7 Templates

Template Structure

It is strongly recommended to extend `projectroles/project_base.html` in your project app templates. Just start your template with the following line:

```
{% extends 'projectroles/project_base.html' %}
```

The following **template blocks** are available for overriding or extending when applicable:

- `title`: Page title
- `css`: Custom CSS (extend with `{{ block.super }}`)
- `projectroles_extend`: Your app content goes here!
- `javascript`: Custom Javascript (extend with `{{ block.super }}`)
- `head_extend`: Optional block if you need to include additional content inside the HTML `<head>` element

Within the `projectroles_extend` block, it is recommended to use the following div classes, both extending the Bootstrap 4 `container-fluid` class:

- `sodar-subtitle-container`: Container for the page title
- `sodar-content-container`: Container for the actual content of your app

Rules

To control user access within a template, just do it as follows:

```
{% load rules %}
{% has_perm 'app.do_something' request.user project as can_do_something %}
```

This checks if the current user from the HTTP request has permission for `app.do_something` in the current project retrieved from the page context.

Template Tags

General purpose template tags are available in `projectroles/templatetags/projectroles_common_tags.py`. Include them to your template as follows:

```
{% load projectroles_common_tags %}
```

Example

Minimal example for a project app template:

```
{% extends 'projectroles/project_base.html' %}

{% load projectroles_common_tags %}
{% load rules %}

{% block title %}
    Page Title
{% endblock title %}
```

(continues on next page)

(continued from previous page)

```
{% block head_extend %}
    {% OPTIONAL: extra content under <head> goes here %}
{% endblock head_extend %}

{% block css %}
    {{ block.super }}
    {% OPTIONAL: Extend or override CSS here %}
{% endblock css %}

{% block projectroles_extend %}

    {% Page subtitle %}
    <div class="container-fluid sodar-subtitle-container">
        <h3><i class="fa fa-rocket"></i> App and/or Page Title</h3>
    </div>

    {% App content %}
    <div class="container-fluid sodar-page-container">
        <p>Your app content goes here!</p>
    </div>

{% endblock projectroles_extend %}

{% block javascript %}
    {{ block.super }}
    {% OPTIONAL: include additional Javascript here %}
{% endblock javascript %}
```

See `example_project_app/example.html` for a working and fully commented example of a minimal template.

Hint: If you include some controls on your `sodar-subtitle-container` class and want it to remain sticky on top of the page while scrolling, use `row` instead of `container-fluid` and add the `bg-white sticky-top` classes to the element.

13.2.8 General Guidelines for Views and Templates

General guidelines and hints for developing views and templates are discussed in this section.

Referring to Project Type

As of SODAR Core v0.4.3, it is possible to customize the display name for the project type from the default “project” or “category”. For more information, see [Projectroles Customization](#).

It is thus recommended that instead of hard coding “project” or “category” in your views or templates, use the `get_display_name()` function to refer to project type.

In templates, this can be achieved with a custom template tag. Example:

```
{% load projectroles_common_tags %}
{% get_display_name project.type title=True plural=False %}
```

In views and other Python code, the similar function can be accessed through `utils.py`:

```
from projectroles.utils import get_display_name
display_name = get_display_name(project.type, plural=False)
```

Hint: If not dealing with a `Project` object, you can provide the `PROJECT_TYPE_*` constant from `SODAR_CONSTANTS`. In templates, it's most straightforward to use "CATEGORY" and "PROJECT".

13.2.9 Forms

This section contains guidelines for implementing forms.

SODAR User Selection Field

Projectroles offers a custom field, widget and accompanying Ajax API views for autocomplete-enabled selection of SODAR users in Django forms. The field will handle providing appropriate choices according to the view context and user permissions, also allowing for customization.

The recommended way to use the built-in user form field is by using the `SODARUserChoiceField` class found in `projectroles.forms`. The field extends Django's `ModelChoiceField` and takes most of the same keyword arguments in its init function, with the exception of `queryset`, `to_field_name`, `limit_choices_to` and `widget` which will be overridden.

The init function also takes new arguments which are specified below:

- **scope:** Scope of users to include (string)
 - `all`: All users on the site
 - `project`: Limit search to users in given project
 - `project_exclude`: Exclude existing users of given project
- `project`: Project object or project UUID string (optional)
- `exclude`: List of User objects or User UUIDs to exclude (optional)
- `forward`: Parameters to forward to autocomplete view (optional)
- `url`: Autocomplete ajax class override (optional)
- `widget_class`: Widget class override (optional)

Below is an example of the classes usage. Note that you can also define the field as a form class member, but the `project` or `exclude` values are not definable at that point. The following example assumes you are setting up your project app form with an extra `project` argument.

```
from projectroles.forms import SODARUserChoiceField

class YourForm(forms.ModelForm):
    class Meta:
        # ...
    def __init__(self, project, *args, **kwargs):
        # ...
        self.fields['user'] = SODARUserChoiceField(
            label='User',
            help_text='Select user for your thing here',
            required=True,
```

(continues on next page)

(continued from previous page)

```
scope='project',
project=project,
exclude=[unwanted_user]
)
```

For more examples of usage of this field and its widget, see `projectroles.forms`. If the field class does not suit your needs, you can also retrieve the related widget to your own field with `projectroles.forms.get_user_widget()`.

The following `django-autocomplete-light` and `select2` CSS and Javascript links have to be added to the HTML template that includes the form with your user selection field:

```
{% block javascript %}
  {{ block.super }}
  <!-- DAL for autocomplete widgets -->
  <script type="text/javascript" src="{% static 'autocomplete_light/jquery.init.js' %}"></script>
  <script type="text/javascript" src="{% static 'autocomplete_light/autocomplete.init.js' %}"></script>
  <script type="text/javascript" src="{% static 'autocomplete_light/vendor/select2/dist/js/select2.full.js' %}"></script>
  <script type="text/javascript" src="{% static 'autocomplete_light/select2.js' %}"></script>
{% endblock javascript %}

{% block css %}
  {{ block.super }}
  <!-- Select2 theme -->
  <link href="https://cdnjs.cloudflare.com/ajax/libs/select2/4.0.6-rc.0/css/select2.min.css" rel="stylesheet" />
{% endblock css %}
```

If using a customized widget with its own Javascript, include the corresponding JS file instead of `autocomplete_light/select2.js`. See the `django-autocomplete-light` documentation for more information on how to customize your autocomplete-widget.

13.2.10 Specific Views and Templates

A few specific views/templates are expected to be implemented.

App Entry Point

As described in the Plugins chapter, an app entry point view is to be defined in the `ProjectAppPlugin`. This is **mandatory**.

The view **must** take a `project` URL kwarg which corresponds to a `Project.sodar_uuid`.

For an example, see `example_project_app.views.ExampleView` and the associated template.

Project Details Element

A sub-template to be included in the project details page (the project's "front page" provided by `projectroles`, where e.g. overview of app content is shown).

Traditionally these files are called `_details_card.html`, but you can name them as you wish and point to the related template in the `details_template` variable of your plugin.

It is expected to have the content in a `card-body` container:

```
<div class="card-body">
    {# Content goes here #}
</div>
```

13.2.11 Project Search Function and Template

If you want to implement search in your project app, you need to implement the `search()` function in your plugin as well as a template for displaying the results.

Hint: Implementing search *can* be complex. If you have access to the main SODAR repository, apps in that project might prove useful examples.

The `search()` Function

See the signature of `search()` in `projectroles.plugins.ProjectAppPluginPoint`. The arguments are as follows:

- **search_term**
 - Term to be searched for (string). Should be self-explanatory.
 - Multiple strings or separating multiple phrases with quotation marks not yet supported.
- **user**
 - User object for user initiating search
- **search_type**
 - The type of object to search for (string, optional)
 - Used to restrict search to specific types of objects
 - You can specify supported types in the plugin's `search_types` list.
 - Examples: `file`, `sample`..
- **keywords**
 - Special search keywords, e.g. "exact"
 - **NOTE:** Currently not implemented

Note: Within this function, you are expected to verify appropriate access of the searching user yourself!

The return data is a dictionary, which is split by groups in case your app can return multiple different lists for data. This is useful where e.g. the same type of HTML list isn't suitable for all returnable types. If only returning one type of data, you can just use e.g. `all` as your only category. Example of the result:

```
return {
  'all': {
    'title': 'List title',      # 1-N categories to be included
                                # Title of the result list to be displayed
    'search_types': [],        # Object types included in this category
    'items': []                # The actual objects returned
  }
}
```

Search Template

Projectroles will provide your template context the `search_results` object, which corresponds to the result dict of the aforementioned function. There are also includes for formatting the results list, which you are encouraged to use.

Example of a simple results template, in case of a single `all` category:

```
{% if search_results.all.items|length > 0 %}

  {# Include standard search list header here #}
  {% include 'projectroles/_search_header.html' with search_title=search_results.all.
    title result_count=search_results.all.items|length %}

  {# Set up a table with your results #}
  <table class="table table-striped sodar-card-table sodar-search-table" id="sodar-
    ff-search-table">
    <thead>
      <tr>
        <th>Name</th>
        <th>Some Other Field</th>
      </tr>
    </thead>
    <tbody>
      {% for item in search_results.all.items %}
        <tr>
          <td>
            <a href="#link_to_somewhere_in_your_app">{{ item.name }}</a>
          </td>
          <td>
            {{ item.some_other_field }}
          </td>
        </tr>
      {% endfor %}
    </tbody>
  </table>

  {# Include standard search list footer here #}
  {% include 'projectroles/_search_footer.html' %}

{% endif %}
```

13.2.12 Tour Help

SODAR Core uses [Shepherd](#) to present an optional interactive tour for a rendered page. To enable the tour in your template, set it up inside the `javascript` template block. Within an inline javascript structure, set the `tourEnabled` variable to `true` and add steps according to the [Shepherd documentation](#).

Example:

```
{% block javascript %}
  {{ block.super }}

  {# Tour content #}
  <script type="text/javascript">
    tourEnabled = true;

    /* Normal step */
    tour.addStep('id_of_step', {
      title: 'Step Title',
      text: 'Description of the step',
      attachTo: '#some-element top',
      advanceOn: '.docs-link click',
      showCancelLink: true
    });

    /* Conditional step */
    if ($('#potentially-existing-element').length) {
      tour.addStep('id_of_another_step', {
        title: 'Another Title',
        text: 'Another description here',
        attachTo: '.potentially-existing-element right',
        advanceOn: '.docs-link click',
        showCancelLink: true
      });
    }

  </script>
{% endblock javascript %}
```

Warning: Make sure you call `{{ block.super }}` at the start of the declared javascript block or you will overwrite the site's default Javascript setup!

13.2.13 API Views

API View usage will be explained in this chapter, currently under construction.

Warning: A unified SODAR API is currently under development and will be documented once stable. Current practices and base classes for API views are subject to change!

Ajax API Views

To set up Ajax API views for the UI, you can use the standard login and project permission mixins along with `APIPermissionMixin` together with any Django Rest Framework view class. Permissions can be managed as with normal Django views. Example with generic `APIView`:

```
from rest_framework.views import APIView
from projectroles.views import (
    LoginRequiredMixin,
```

(continues on next page)

(continued from previous page)

```
        ProjectPermissionMixin,
        APIPermissionMixin,
    )

    class ExampleAjaxAPIView(
        LoginRequiredMixin,
        ProjectPermissionMixin,
        APIPermissionMixin,
        APIView,
    ):

        permission_required = 'projectroles.view_project'

    def get(self, request):
        # ...
```

13.2.14 Removing a Project App

Removing a project app from your Django site can be slightly more complicated than removing a normal non-SODAR-supporting Django application. Following the procedure detailed here you are able to cleanly remove a project app which has been in use on your site.

The instructions apply to project apps you have created yourself as well as project apps included in the django-sodar-core package, with the exception of `projectroles` which can not be removed from a SODAR based site.

Warning: Make sure to perform these steps **in the order they are presented here**. Otherwise you may risk serious problems with your site functionality or your database!

Note: Just in case, it is recommended to make a backup of your Django database before proceeding.

First you should delete all Timeline references to objects in your app. This is not done automatically as, by design, the references are kept even after the original objects are deleted. Go to the Django shell via management command using `shell` or `shell_plus` and enter the following. Replace `app_name` with the name of your application as specified in its `ProjectAppPlugin`.

```
from timeline.models import ProjectEvent
ProjectEvent.objects.filter(app='app_name').delete()
```

Next you should delete existing database objects defined by the models in your app. This is also most easily done via the Django shell. Example:

```
from yourapp.models import YourModel
YourModel.objects.all().delete()
```

After the objects have been deleted, reset the database migrations of your application.

```
$ ./manage.py migrate yourapp zero
```

Once this has been executed successfully, you should delete the plugin object for your application. Returning to the Django shell, type the following:

```
from djangoplugins.models import Plugin
Plugin.objects.get(name='app_name').delete()
```

Finally, you should remove the references to the removed app in the Django configuration.

App dependency in `config/settings/base.py`:

```
LOCAL_APPS = [
    # The app you are removing
    'yourapp.apps.YourAppConfig',
    # ...
]
```

App URL patterns in `config/urls.py`:

```
urlpatterns = [
    # Your app's URLs
    url(r'^yourapp/', include('yourapp.urls')),
    # ...
]
```

Once you have performed the aforementioned database operations and deployed a version of your Django site with the application dependency and URL patterns removed, the project app should be cleanly removed from your site.

13.2.15 TODO

- Naming conventions
- Examples of recurring template styles (e.g. forms)

13.3 Site App Development

This document details instructions and guidelines for developing **site apps** to be used with the SODAR Core framework.

It is recommended to read *Project App Development* before this document.

13.3.1 Site App Basics

Site apps are basically normal Django apps *not* hooked to SODAR projects. However, they provide a few nice features to be used in a SODAR-enabled Django site:

- Rules for accessing app data (similar to project apps but without the need for being associated with a project)
- Dynamic inclusion into the site and default templates via plugins
- The ability to show site-wide messages to users

13.3.2 Prerequisites

See *Project App Development*.

13.3.3 Models

No specific model implementation is required. However, it is strongly to refer to objects using `sodar_uuid` fields instead of the database private key.

13.3.4 Rules File

Generate a `rules.py` file similar to a project app. However, you should not use project predicates in this one. Example:

```
import rules
# Allow viewing data
rules.add_perm('{APP_NAME}.view_data', rules.is_authenticated)
```

13.3.5 SiteAppPlugin

Create a file `plugins.py` in your app's directory. In the file, declare a `SiteAppPlugin` class implementing `projectroles.plugins.SiteAppPluginPoint`. Within the class, implement member variables and functions as instructed in comments and docstrings.

```
from projectroles.plugins import SiteAppPluginPoint
from .urls import urlpatterns

class SiteAppPlugin(SiteAppPluginPoint):
    """Plugin for registering a site-wide app"""
    name = 'example_site_app'
    title = 'Example Site App'
    urls = urlpatterns
    # ...
```

The following variables and functions are **mandatory**:

- `name`: App name (ideally should correspond to the app package name)
- `title`: Printable app title
- `urls`: Urlpatterns (usually imported from the app's `urls.py` file)
- `icon`: Font Awesome 4.7 icon name (without the `fa-*` prefix)
- `entry_point_url_id`: View ID for the app entry point
- `description`: Verbose description of app
- `app_permission`: Basic permission for viewing app data in project (see above)

Implementing the following is **optional**:

- `app_settings`: Implement if project or user specific settings for the app are needed. See the plugin point definition for an example.
- `get_messages()`: Implement if your site app needs to display site-wide messages for users.

13.3.6 Views

In your views, you can still use projectroles mixins which are *not* related to projects. Especially `LoggedInPermissionMixin` is useful to ensure users not allowed to access a view are properly redirected. Example:

```
from django.views.generic import TemplateView
from projectroles.views import LoggedInPermissionMixin

class ExampleView(LoginPermissionMixin, TemplateView):
    """Site app example view"""
    permission_required = 'example_site_app.view_data'
    template_name = 'example_site_app/example.html'
```

Note: The entry point URL is not expected to have any URL kwargs in the current implementation. If you intend to use a view which makes use of URL kwargs, you may need to modify it into also accepting a request without any parameters (e.g. displaying default content for the view).

13.3.7 Templates

It is recommended for you to extend `projectroles/base.html` and put your actual app content within the `projectroles` block. Example:

```
{# Projectroles dependency #}
{% extends 'projectroles/base.html' %}
{% load projectroles_common_tags %}

{% block title %}
    Example Site App Page Title
{% endblock title %}

{% block projectroles %}

    <div class="container sodar-subtitle-container">
        <h2><i class="fa fa-umbrella"></i> Example Site App</h2>
    </div>

    <div class="container-fluid sodar-page-container">
        <div class="alert alert-info">
            This is an example and the entry point for <code>example_site_app</code>.
        </div>
    </div>

{% endblock projectroles %}
```

13.3.8 Site App Messages

The site app provides a way to display certain messages to users. For this, you need to implement `get_messages()` in the `SiteAppPlugin` class.

If you need to control e.g. which user should see the message or removal of a message after showing, you need to implement relevant logic in the function.

Example:

```
def get_messages(self, user=None):
    """
    Return a list of messages to be shown to users.
    :param user: User object (optional)
    :return: List of dicts or and empty list if no messages
    """
    return [{
        'content': 'Message content in here, can contain html',
        'color': 'info',          # Corresponds to bg-* in Bootstrap
        'dismissable': True      # False for non-dismissable
        'require_auth': True     # Only view for authorized users
    ]}
```

13.4 Backend App Development

This document details instructions and guidelines for developing **backend apps** to be used with the SODAR Core framework.

It is recommended to read *Project App Development* before this document.

13.4.1 Backend App Basics

Backend apps are intended as apps used by other apps via their plugin, without requiring hard-coded imports. These may provide their own views for e.g. Ajax API functionality, but mostly they're intended to be internal (hence the name).

13.4.2 Prerequisites

See *Project App Development*.

13.4.3 Models

No specific model implementation is required. However, it is strongly to refer to objects using `sodar_uuid` fields instead of the database private key.

13.4.4 BackendAppPlugin

The plugin is detected and retrieved using a `BackendAppPlugin`.

Declaring the Plugin

Create a file `plugins.py` in your app's directory. In the file, declare a `BackendAppPlugin` class implementing `projectroles.plugins.BackendPluginPoint`. Within the class, implement member variables and functions as instructed in comments and docstrings.


```

from projectroles.plugins import BackendPluginPoint
from .urls import urlpatterns

class BackendAppPlugin(BackendPluginPoint):
    """Plugin for registering a backend app"""
    name = 'example_backend_app'
    title = 'Example Backend App'
    urls = urlpatterns
    # ...

```

The following variables and functions are **mandatory**:

- `name`: App name (ideally should correspond to the app package name)
- `title`: Printable app title
- `icon`: Font Awesome 4.7 icon name (without the `fa-*` prefix)
- `description`: Verbose description of app
- `get_api()`: Function for retrieving the API class for the backend, to be implemented

Implementing the following is **optional**:

- `javascript_url`: Path to on demand includeable Javascript file
- `css_url`: Path to on demand includeable CSS file
- `get_statistics()`: Return statistics for the siteinfo app. See details in *the siteinfo documentation*.

Hint: If you want to implement a backend API which is closely tied to a project app, there's no requirement to declare your backend as a separate Django app. You can just include the `BackendAppPlugin` in your app's `plugins.py` along with your `ProjectAppPlugin`. See the *timeline app* for an example of this.

Using the Plugin

To retrieve the API for the plugin, use the function `projectroles.plugins.get_backend_api()` as follows:

```

from projectroles.plugins import get_backend_api
example_api = get_backend_api('example_backend_app')

if example_api:      # Make sure the API is there, and only after that..
    pass             # ..do stuff with the API

```

Including Backend Javascript/CSS

If you want Javascript or CSS files to be associated with your plugin you can set the `javascript_url` or `css_url` variables to specify the path to your file. Note that these should correspond to `STATIC` paths under your app directory.

```

class BackendPlugin(BackendPluginPoint):

    name = 'example_backend_app'
    title = 'Example Backend App'
    javascript_url = 'example_backend_app/js/example.js'
    css_url = 'example_backend_app/css/example.css'

```

The `get_backend_include` template-tag will return a `<script>` or `<link>` html tag with your specific file path, to be used in a template of your app making use of the backend plugin:

```
{% load projectroles_common_tags %}
{% get_backend_include 'example_backend_app' 'js' as javascript_include_tag %}
{{ javascript_include_tag|safe }}

{% get_backend_include 'example_backend_app' 'css' as css_include_tag %}
{{ css_include_tag|safe }}
```

This will result in the following HTML:

```
<script type="text/javascript" src="/static/example.js"></script>
<link rel="stylesheet" type="text/css" href="/static/example.css"/>
```

Be sure to use the backend plugin's name (not the title) as the key and filter the result by `safe`, so the tag won't be auto-escaped.

13.5 SODAR Core Development

This document details instructions and guidelines for development of the SODAR Core package.

13.5.1 Repository Contents

In addition to the apps which will be installed by the package, the following directories are included in the repository for development use and as examples:

- **config:** Example Django site configuration
- **docs:** Usage and development documentation
- **example_backend_app:** Example SODAR Core compatible backend app
- **example_project_app:** Example SODAR Core compatible project app
- **example_site:** Example SODAR Core based Django site for development
- **example_site_app:** Example SODAR Core compatible site-wide app
- **requirements:** Requirements for SODAR Core and development
- **utility:** Setup scripts for development

13.5.2 Installation

Instructions on how to install a local development version of SODAR Core are detailed here. Ubuntu 16.04 LTS (Xenial) is the supported OS at this time. Later Ubuntu versions and Centos 7 have also been proven to work, but some system dependencies may vary for different OS versions or distributions.

Installation and development should be possible on most recent versions of Linux, Mac and Windows, but this may require extra work and your mileage may vary.

If you need to set up the accompanying example site in Docker, please see online for up-to-date Docker setup tutorials for Django related to your operating system of choice.

System Installation

First you need to install OS dependencies, PostgreSQL 9.6 and Python3.6.

```
$ sudo utility/install_os_dependencies.sh
$ sudo utility/install_python.sh
$ sudo utility/install_postgres.sh
```

Database Setup

Next you need to setup the database and postgres user. You'll be prompted to enter a database name, a username and a password.

```
$ sudo utility/setup_database.sh
```

You have to set the database URL and credentials for Django in the environment variable `DATABASE_URL`. For development it is recommended to place environment variables in file `.env` located in your project root. To enable loading the file in Django, set `DJANGO_READ_DOT_ENV_FILE=1` in your environment variables when running SODAR or any of its management commands. See `config/settings/base.py` for more information and the `env.example` file for an example environment file.

Example of the database URL variable as set within an `.env` file:

```
DATABASE_URL=postgres://sodar_core:sodar_core@127.0.0.1/sodar_core
```

Project Setup

Clone the repository, setup and activate the virtual environment. Once in the environment, install Python requirements for the project:

```
$ git clone git+https://github.com/bihealth/sodar_core.git
$ cd sodar_core
$ pip install virtualenv
$ virtualenv -p python3.6 .venv
$ source .venv/bin/activate
$ utility/install_python_dependencies.sh
```

LDAP Setup (Optional)

If you will be using LDAP/AD auth on your site, make sure to also run:

```
$ sudo utility/install_ldap_dependencies.sh
$ pip install -r requirements/ldap.txt
```

Final Setup

Initialize the database (this will also synchronize django-plugins):

```
$ ./manage.py migrate
```

Create a Django superuser for the `example_site`:

```
$ ./manage.py createsuperuser
```

Now you should be able to run the server:

```
$ ./run.sh
```

13.5.3 Testing

To run unit tests, you have to install the headless Chrome driver (if not yet present on your system), followed by the Python test requirements:

```
$ sudo utility/install_chrome.sh  
$ pip install -r requirements/test.txt
```

Now you can run all tests with the following script:

```
$ ./test.sh
```

If you want to only run a certain subset of tests, use e.g.:

```
$ ./test.sh projectroles.tests.test_views
```

For running tests with SODAR Taskflow (not currently publicly available), you can use the supplied shortcut script:

```
$ ./test_taskflow.sh
```

13.5.4 Contributing

SODAR Core is currently in active development in a private BIH repository. The public GitHub repository is primarily intended for publishing stable releases. Furthermore, the issue IDs within the code and documentation point to our private issue tracker unless otherwise mentioned.

MAJOR CHANGES

This document details highlighted updates and breaking changes in SODAR Core releases. It is recommended to review these notes whenever upgrading from an older SODAR Core version. For a complete list of changes in current and previous releases, see the [full changelog](#).

14.1 v0.7.2 (2020-01-31)

14.1.1 Release Highlights

- Enforce API versions in remote project sync
- Separate base API views for SODAR Core API and external SODAR site APIs
- Redesign user autocomplete field
- Set issuing user email to `reply-to` header for role and invite emails
- Display hidden project app settings to superusers in project update form
- Allow providing custom keyword arguments for backend plugin `get_api()` through `get_backend_api()`
- Enable sorting custom project list columns in plugin definition
- Bug fixes for project list columns

14.1.2 Breaking Changes

User Autocomplete Field Redesigned

User autocomplete field for forms with its related widget(s) have been redesigned with breaking API changes. Please review the [Project App Development](#) documentation and modify your implementation accordingly.

Remote Project Sync API Version Enforcing

The remote project sync view initiated from a `TARGET` site now sends the version number, making the `SOURCE` site enforce allowed API versions in its request. Hence, when a major breaking change is made on the source site and version requirements updated, requests from the target site will no longer work without upgrading to the latest SODAR Core version.

Exceptions Raised by `get_backend_api()`

The `get_backend_api()` method for retrieving backend plugin API objects no longer suppresses potential exceptions raised by API object initialization. If it is possible for your API object to raise an exception on initialization, you will need to handle it when calling this method.

System Prerequisites

The minimum version requirement for Django has been bumped to 1.11.27.

KnoxAuthMixin in Tests

Default API configuration for methods in `KnoxAuthMixin` are now set to internal SODAR Core API values. If you use the mixin in the tests of your site, please update the arguments in your method calls accordingly. You can also now supply the `media_type` argument for relevant functions. The `get_accept_header()` method has been moved to a separate `SODARAPIViewMixin` helper mixin.

14.2 v0.7.1 (2019-12-18)

14.2.1 Release Highlights

- Project list layout and extra column handling improved
- Allow customizing widgets in app settings
- Enable managing global JS/CSS includes in Django settings
- Initial support for deploying site in kiosk mode
- Critical bug fixes for category and project owner management

14.2.2 Breaking Changes

Default Templates Modified

The default templates `base_site.html` and `login.html` have been modified in this version. If you override them with your own altered versions, please review the difference and update your templates as appropriate.

User Added to `get_project_list_value()`

The signature of the `get_project_list_value()` method implemented by project app plugins to return data for extra project list columns has changed. The `user` argument which provides the current user has been added. If using this feature, please make sure to update your implementation(s) of the method.

See [Projectroles API Documentation](#) to review the API changes.

14.3 v0.7.0 (2019-10-09)

14.3.1 Release Highlights

- Sync peer project information for remote target sites
- Enable revoking access to remote projects
- Allow defining app settings in site apps
- “User in project” scope added into app settings
- Support JSON in app settings
- Project owner management moved to project member views

14.3.2 Breaking Changes

System Prerequisites

The minimum supported versions have been upgraded for a number of Python packages in this release. It is highly recommended to also upgrade these for your SODAR Core based site. See the `requirements` directory for up-to date dependencies.

Backend Javascript Include

The code in `base.html` which was including javascript from backend apps to all templates in `projectroles` was removed. Instead, Javascript and CSS associated to a backend plugin should now be included in app templates as needed. This is done using the newly introduced `get_backend_include()` template tag in `projectroles_common_tags`.

Deprecated `get_setting()` Tag Removed

The deprecated `get_setting()` template tag has been removed from `projectroles_common_tags`. Please use `get_django_setting()` in your templates instead.

ProjectSettingMixin Removed

In `projectroles.tests.test_views`, the deprecated `ProjectSettingMixin` was removed. If you need to populate app settings in your tests, use the `AppSettingAPI` instead.

AppSettingAPI `get_setting_defs()` Signature Changed

The `get_settings_defs()` function in the app settings API now accepts either a project app plugin or simply the name of the plugin as string. Due to this change, the signature of the API function including argument order has changed. Please see the [API documentation](#) for more details and update your function calls accordingly.

Default Footer Styling Changed

The styling of the page footer and the default `_footer.html` have changed. You no longer need an extra `<div>` element for the footer content, unless you need to do styling overrides yourself.

14.4 v0.6.2 (2019-06-21)

14.4.1 Release Highlights

- Allow hiding app settings from UI forms
- Add template tag for retrieving app settings

14.4.2 Breaking Changes

System Prerequisites

The minimum version requirement for Django has been bumped to 1.11.21.

Template Tag for Django Settings Access Renamed

The `get_setting()` template tag in `projectroles_common_tags` has been renamed into `get_django_setting()`. In this version the old tag still works, but this deprecation protection will be removed in the next release. Please update any references to this tag in your templates.

14.5 v0.6.1 (2019-06-05)

14.5.1 Release Highlights

- Add custom project list columns definable in `ProjectAppPlugin`
- Add example project list column implementation in the `filesfolders` app

14.5.2 Breaking Changes

App Settings Deprecation Protection Removed

The deprecation protection set up in the previous release has been removed. Project app plugins are now expected to declare `app_settings` in the format introduced in v0.6.0.

14.6 v0.6.0 (2019-05-10)

14.6.1 Release Highlights

- Add user specific settings
- Refactor project settings into project/user specific app settings
- Add `siteinfo` app

14.6.2 Breaking Changes

App Settings (Formerly Project Settings)

The former Project Settings module has been completely overhauled in this version and requires changes to your app plugins.

The `projectroles.project_settings` module has been renamed into `projectroles.app_settings`. Please update your dependencies accordingly.

Settings must now be defined in `app_settings`. The format is identical to the previous `project_settings` dictionary, except that a `scope` field is expected for each settings. Currently valid values are “PROJECT” and “USER”. It is recommended to use the related constants from `SODAR_CONSTANTS` instead of hard coded strings.

Example of settings:

```
#: Project and user settings
app_settings = {
    'project_bool_setting': {
        'scope': 'PROJECT',
        'type': 'BOOLEAN',
        'default': False,
        'description': 'Example project setting',
    },
    'user_str_setting': {
        'scope': 'USER',
        'type': 'STRING',
        'label': 'String example',
        'default': '',
        'description': 'Example user setting',
    },
}
```

Warning: Deprecation protection is place in this version for retrieving settings from `project_settings` if it has not been changed into `app_settings` in your project apps. This protection **will be removed** in the next SODAR Core release.

14.7 v0.5.1 (2019-04-16)

14.7.1 Release Highlights

- Sodarcache refactoring and improvements for API, models, management and app config
- New default error templates

14.7.2 Breaking Changes

Site App Templates

Templates for **site apps** should extend `projectroles/base.html`. In earlier versions the documentation erroneously stated `projectroles/project_base.html` as the base template to use. Extending that document does work in this version as long as you override the given template blocks. However, it is not recommended and may break in the future.

Sodarcache App Changes

The following potentially breaking changes have been made to the sodarcache app.

App configuration naming has been changed to `sodarcache.apps.SodarcacheConfig`. Please update `config/settings/base.py` accordingly.

The field `user` has been made optional in models and the API.

An optional `user` argument has been added to `ProjectAppPlugin.update_cache()`. Correspondingly, the similar argument in `ProjectCacheAPI.set_cache_item()` has been made optional. Please update your plugin implementations and function calls accordingly.

The `updatecache` management command has been renamed to `synccache`.

Helper `get_app_names()` Fixed

The `projectroles.utils.get_app_names()` function will now return nested app names properly instead of omitting everything beyond the topmost module.

Default Admin Setting Deprecation Removed

The `PROJECTROLES_ADMIN_OWNER` setting no longer works. Use `PROJECTROLES_DEFAULT_ADMIN` instead.

14.8 v0.5.0 (2019-04-03)

14.8.1 Release Highlights

- New sodarcache app for caching and aggregating data from external services
- Local user mode for site UI and remote sync
- Improved display and logging of remote project sync
- Upgrade to Bootstrap 4.3.1

14.8.2 Breaking Changes

Default Admin Setting Renamed

The setting `PROJECTROLES_ADMIN_OWNER` has been renamed into `PROJECTROLES_DEFAULT_ADMIN` to better reflect its uses. Please rename this settings variable on your site configuration to prevent issues.

Note: In this release, the old settings value is still accepted in remote project management to avoid sudden crashes. This deprecation will be removed in the next release.

Bootstrap 4.3.1 Upgrade

The Bootstrap and Popper dependencies have been updated to the latest versions. Please test your site to make sure this does not result in compatibility issues. The known issue of HTML content not showing in popovers has already been fixed in `projectroles.js`.

Default Templates Modified

The default templates `base_site.html` and `login.html` have been modified in this version. If you override them with your own altered versions, please review the difference and update your templates as appropriate.

14.9 v0.4.5 (2019-03-06)

14.9.1 Release Highlights

- Add user autocomplete in forms
- Allow multiple delegates per project

14.9.2 Breaking Changes

System Prerequisites

The minimum version requirement for Django has been bumped to 1.11.20.

User Autocomplete Widget Support

Due to the use of autocomplete widgets for users, the following apps must be added into `THIRD_PARTY_APPS` in `config/settings/base.py`, regardless of whether you intend to use them in your own apps:

```
THIRD_PARTY_APPS = [  
    # ...  
    'dal',  
    'dal_select2',  
]
```

Project.get_delegate() Helper Renamed

As the limit for delegates per project is now arbitrary, the `Project.get_delegate()` helper function has been replaced by `Project.get_delegates()`. The new function returns a `QuerySet`.

Bootstrap 4 Crispy Forms Overrides Removed

Deprecated site-wide Bootstrap 4 theme overrides for `django-crispy-forms` were removed from the example site and are no longer supported. These workarounds were located in `{SITE_NAME}/templates/bootstrap4/`. Unless specifically required forms on your site, it is recommended to remove the files from your project.

Note: If you choose to keep the files or similar workarounds in your site, you are responsible of maintaining them and ensuring SODAR compatibility. Such site-wide template overrides are outside of the scope for SODAR Core components. Leaving the existing files in without maintenance may cause undesirable effects in the future.

Database File Upload Widget

Within SODAR Core apps, the only known issue caused by removal of the aforementioned Bootstrap 4 form overrides in the file upload widget of the `django-db-file-upload` package. If you are using the file upload package in your own SODAR apps and have removed the site-wide Crispy overrides, you can fix this particular widget by adding the following snippet into your form template. Make sure to replace `{FIELD_NAME}` with the name of your form field.

```
{% block css %}
  {{ block.super }}
  {# Workaround for django-db-file-storage Bootstrap4 issue (#164) #}
  <style type="text/css">
    div#div_id_{FIELD_NAME} div p.invalid-feedback {
      display: block;
    }
  </style>
{% endblock css %}
```

Alternatively, you can create a common override in your project-wide CSS file.

14.10 v0.4.4 (2019-02-19)

14.10.1 Release Highlights

N/A (maintenance/bugfix release)

14.10.2 Breaking Changes

Textarea Height in Forms

Due to this feature breaking the layout of certain third party components, textarea height in forms is no longer adjusted automatically. An exception to this are Pagedown-specific markdown fields.

To adjust the height of a textarea field in your forms, the easiest way is to modify the widget of the related field in the `__init__()` function of your form as follows:

```
self.fields['field_name'].widget.attrs['rows'] = 4
```

14.11 v0.4.3 (2019-01-31)

14.11.1 Release Highlights

- Add display name configuration for projects and categories
- Hide immutable fields in projectroles forms

14.11.2 Breaking Changes

SODAR Constants

`PROJECT_TYPE_CHOICES` has been removed from `SODAR_CONSTANTS`, as it can vary depending on implemented `DISPLAY_NAMES`. If needed, the currently applicable form structure can be imported from `projectroles.forms`.

14.12 v0.4.2 (2019-01-25)

14.12.1 Release Highlights

N/A (maintenance/bugfix release)

14.12.2 Breaking Changes

System Prerequisites

The following minimum version requirements have been upgraded in this release:

- Django 1.11.18+
- Bootstrap 4.2.1
- JQuery 3.3.1
- Numerous required Python packages (see `requirements/*.txt`)

Please go through your site requirements and update dependencies accordingly. For project stability, it is still recommended to use exact version numbers for Python requirements in your SODAR Core based site.

If you are overriding the `projectroles/base_site.html` in your site, make sure to update Javascript and CSS includes accordingly.

Note: Even though the recommended Python version from Django 1.11.17+ is 3.7, we only support Python 3.6 for this release. The reason is that some dependencies still exhibit problems with the most recent Python release at the time of writing.

ProjectAccessMixin

The `_get_project()` function in `ProjectAccessMixin` has been renamed into `get_project()`. Arguments for the function are now optional and may be removed in a subsequent release: `self.request` and `self.kwargs` of the view class will be used if the arguments are not present.

Base API View

The base SODAR API view has been renamed from `BaseAPIView` into `SODARAPIBaseView`.

Taskflow Backend API

The `cleanup()` function in `TaskflowAPI` now correctly raises a `CleanupException` if SODAR Taskflow encounters an error upon calling its cleanup operation. This change should not affect normally running your site, as the function in question should only be called during Taskflow testing.

14.13 v0.4.1 (2019-01-11)

14.13.1 Release Highlights

- Configuration updates for API and Projectroles
- Travis-CI setup

14.13.2 Breaking Changes

System Prerequisites

Changes in system requirements:

- **Ubuntu 16.04 Xenial** is the target OS version.
- **Python 3.6 or newer required:** 3.5 and older releases no longer supported.
- **PostgreSQL 9.6** is the recommended minimum version for the database.

Site Messages in Login Template

If your site overrides the default login template in `projectroles/login.html`, make sure your overridden version contains an include for `projectroles/_messages.html`. Following the SODAR Core template conventions, it should be placed as the first element under the `container-fluid` div in the `content` block. Otherwise, site app messages not requiring user authorization will not be visible on the login page. Example:

```
{% block content %}
  <div class="container-fluid">
    {# Django messages / site app messages #}
    {% include 'projectroles/_messages.html' %}
    {# ... #}
  </div>
{% endblock content %}
```

14.14 v0.4.0 (2018-12-19)

14.14.1 Release Highlights

- Add filesfolders app from SODAR v0.4.0
- Add bgjobs app from Varfish-Web
- Secure SODAR Taskflow API views
- Separate test server configuration for SODAR Taskflow
- Extra data variable rendering for timeline
- Additional site settings

14.14.2 Breaking Changes

List Button Classes in Templates

Custom small button and dropdown classes for including buttons within tables and lists have been modified. The naming has also been unified. The following classes should now be used:

- Button group: `sodar-list-btn-group` (formerly `sodar-edit-button-group`)
- Button: `sodar-list-btn`
- Dropdown: `sodar-list-dropdown` (formerly `sodar-edit-dropdown`)

See projectroles templates for examples.

Warning: The standard bootstrap class `btn-sm` should **not** be used with these custom classes!

SODAR Taskflow v0.3.1 Required

If using SODAR Taskflow, this release requires release v0.3.1 or higher due to mandatory support of the `TASKFLOW_SODAR_SECRET` setting.

Taskflow Secret String

If you are using the `taskflow` backend app, you **must** set the value of `TASKFLOW_SODAR_SECRET` in your Django settings. Note that this must match the similarly named setting in your SODAR Taskflow instance!

14.15 v0.3.0 (2018-10-26)

14.15.1 Release Highlights

- Add remote project metadata and member synchronization between multiple SODAR sites
- Add adminalerts app
- Add taskflowbackend app

14.15.2 Breaking Changes

Remote Site Setup

For specifying the role of your site in remote project metadata synchronization, you will need to add two new settings to your Django site configuration:

The `PROJECTROLES_SITE_MODE` setting sets the role of your site in remote project sync and it is **mandatory**. Accepted values are `SOURCE` and `TARGET`. For deployment, it is recommended to fetch this setting from environment variables.

If your site is set in `TARGET` mode, the boolean setting `PROJECTROLES_TARGET_CREATE` must also be included to control whether creation of local projects is allowed. If your site is in `SOURCE` mode, this setting can be included but will have no effect.

Furthermore, if your site is in TARGET mode you must include the PROJECTROLES_ADMIN_OWNER setting, which must point to an existing local superuser account on your site.

Example for a SOURCE site:

```
# Projectroles app settings
PROJECTROLES_SITE_MODE = env.str('PROJECTROLES_SITE_MODE', 'SOURCE')
```

Example for a TARGET site:

```
# Projectroles app settings
PROJECTROLES_SITE_MODE = env.str('PROJECTROLES_SITE_MODE', 'TARGET')
PROJECTROLES_TARGET_CREATE = env.bool('PROJECTROLES_TARGET_CREATE', True)
PROJECTROLES_ADMIN_OWNER = env.str('PROJECTROLES_ADMIN_OWNER', 'admin')
```

General API Settings

Add the following lines to your configuration to enable the general API settings:

```
SODAR_API_DEFAULT_VERSION = '0.1'
SODAR_API_MEDIA_TYPE = 'application/vnd.bihealth.sodar+json'
```

DataTables Includes

Includes for the DataTables Javascript library are no longer included in templates by default. If you want to use DataTables, include the required CSS and Javascript in relevant templates. See the projectroles/search.html template for an example.

SODAR CORE CHANGELOG

Changelog for the **SODAR Core** Django app package. Loosely follows the [Keep a Changelog](#) guidelines.

Note that the issue IDs here refer to ones in the private CUBI GitLab.

15.1 v0.7.2 (2020-01-31)

15.1.1 Added

- **Projectroles**

- `custom_order` argument in `get_active_plugins()` (#431)
- Enable ordering custom project list columns in project app plugin (#427)
- `SODARCoreAPIBaseView` base API view class for internal SODAR Core apps (#442)
- API version enforcing in `RemoteProjectsSyncView` and `syncremote.py` (#444)
- Allow extra keyword arguments in `get_backend_api()` (#397)
- Example usage of `get_backend_api()` extra kwargs in `example_backend_app` (#397)
- `SODARUserChoiceField` and `get_user_widget()` for user selection in forms (#455)
- Setting `reply-to` headers for role change and invite emails (#446)
- No reply note and related `PROJECTROLES_EMAIL_SENDER_REPLY` setting (#446)
- Display hidden project app settings to superusers (#424)

- **Sodarcache**

- Allow limiting `deletecache` to a specific project (#448)

15.1.2 Changed

- **General**

- Upgrade minimum Django version to 1.11.27
- Base `RemoteProjectGetAPIView` on `SODARCoreAPIBaseView` (#442)

- **Bgjobs**

- Make `specialize_job()` more robust (#456)

- **Projectroles**

- Accept null value for `AppSetting.value_json` (#426)
- Use `PluginContextMixin` in `ProjectContextMixin` (#430)
- Move `get_accept_header()` to `SODARAPIViewMixin` (#445)
- Allow exceptions to be raised by `get_backend_plugin()` (#451)
- Improve tour help CSS (#438)
- Field order in `RoleAssignmentOwnerTransferView` (#441)
- Redesign user autocomplete handling in forms (#455)
- Rename `SODARUserAutocompleteWidget` and `SODARUserRedirectWidget` (#455)
- Disable ownership transfer link if owner is the only project user (#454)

15.1.3 Fixed

- **Projectroles**

- Potential crash in `_project_header.html` with ownerless kiosk mode category (#422)
- Form crash when saving a JSON app setting with `user_modifiable=False` (#426)
- Inconsistent plugin ordering in custom project list columns (#428)
- Project app plugins included twice in `HomeView` (#432)
- `ProjectPermissionMixin` query set override with `get_project_filter_key()`
- Search disabled with unchanged input value on search page load (#436)
- Subprojects queried for non-categories in `project_detail.html` (#434)
- Current owner selectable in ownership transfer form (#440)

- **Taskflowbackend**

- Potential crash in `TaskflowAPI` initialization

15.1.4 Removed

- **Projectroles**

- Unused backend plugins queried for context data in `HomeView` (#433)
- Unneeded `UserAutocompleteExcludeMembersAPIView` (#455)

15.2 v0.7.1 (2019-12-18)

15.2.1 Added

- **General**

- Include CHANGELOG in documentation (#379)

- **Projectroles**

- `widget_attrs` parameter for project and user settings (#404)

- Remote project member management link for target projects (#382)
- Current user in `get_project_list_value()` arguments (#413)
- Display category owner in page header (#414)
- Configuring UI test settings via Django settings or `TestUIBase` vars (#417)
- Initial support for deploying site in kiosk mode (#406)
- Optional disabling of default CDN Javascript and CSS includes (#418)
- Defining custom global JS/CSS includes in Django settings (#418)

15.2.2 Changed

- **General**
 - Change “Breaking Changes” doc into “Major Changes” (#201)
 - Refactor and rename ownership transfer classes and template
 - Use RTD theme in documentation (#384)
 - Upgrade to Chromedriver v79
- **Adminalerts**
 - Rename `INACTIVE` alert state in UI (#396)
 - Rename URL name and pattern for activation API view (#378)
 - Improve alert detail page layout (#385)
- **Projectroles**
 - Improve unsupported browser warning (#405)
 - Move project list description into tooltip (#388)
- **Siteinfo**
 - Improve page title and heading (#402)
- **Sodarcache**
 - Clarify management command logging (#403)
- **Timeline**
 - Improve extra data status tab legend (#380)

15.2.3 Fixed

- **General**
 - PPA used for Python 3.6 installs no longer available (#416)
- **Filesfolders**
 - Invalid HTML in project list extra columns
- **Projectroles**
 - Dismissing login error alert in `login.html` not working (#377)
 - Current owner queries incorrectly filtered in `RoleAssignmentOwnerTransferView` (#393)

- Hardcoded project type display name in sent emails (#398)
- Silent failing of invalid app setting type in plugin definition (#390)
- Exception raised by hidden sidebar in sidebar height calculation (#407)
- Crash in `get_default_setting()` if default JSON value was not set (#389)
- Owner widget hidden in category update view (#394)
- Project list extra column header alignment not set (#412)
- `get_project_list_value()` template tag displaying “None” on null value (#411)

15.3 v0.7.0 (2019-10-09)

15.3.1 Added

- **General**

- Development env file example `env.example` (#297)
- Postgres database development setup script (#302)
- `ENABLE_DEBUG_TOOLBAR` setting for local development (#349)
- `local_target2.py` config for peer remote site development (#200)

- **Adminalerts**

- Activate/suspend button in alert list (#42)

- **Bgjobs**

- Pagination for background job list (#335)
- `BGJOBS_PAGINATION` Django setting (#335)

- **Projectroles**

- `get_backend_include()` common template tag (#261)
- `css_url` member variable in `BackendPluginPoint` (#261)
- Example of on-demand Javascript/CSS inclusion in example apps (#261)
- Remote project link display toggle for target sites (#276)
- Project UUID clipboard copying button (#290)
- Support for app settings in site apps (#308)
- Initial implemenetation for common clipboard copying visualization (#333)
- Send email for owner role assignment (#325)
- Common pagination include template `_pagination.html` (#334)
- Synchronization and display of PEER sites in remote site management (#200)
- Link for copying remote site secret token in remote site list (#332)
- Project ownership transfer from member list (#287)
- UI notification for disabled member management on target sites (#301)
- Management command `addremotesite` for adding remote sites (#314)

- JSON support for app settings (#268)
- `get_setting_def()` in app settings API
- Timeline logging of app settings in project creation (#359)
- “Project and user” scope for app settings (#266)
- REVOKED status for remote projects with revoked access (#327)
- `Project.is_revoked()` helper (#327)
- Disabling access for non-owner/delegate for revoked projects in `ProjectPermissionMixin` (#350)
- **Timeline**
 - Display event extra data as JSON (#6)
- **Userprofile**
 - User setting for project UUID clipboard copying (#290, #308)

15.3.2 Changed

- **General**
 - Upgrade Chromedriver to version 77.0.3865.40
 - Use `CurrentUserFormMixin` instead of repeated code (#12)
 - Run tests in parallel where applicable
 - Upgrade minimum Django version to 1.11.25 (#346)
 - General upgrade for Python package requirements (#282)
- **Adminalerts**
 - Use common pagination template
- **Projectroles**
 - Improve user name placeholder in `login.html` (#294)
 - Backend app Javascript and CSS included on-demand instead of for all templates (#261)
 - Make sidebar hiding dynamic by content height (#316)
 - Replace `login_and_redirect()` in UI tests with a faster cookie based function (#323)
 - Refactor remote project display on details page (#196)
 - Refactor `AppSettingAPI` (#268)
 - Enable calling `AppSettingAPI.get_setting_defs()` with app name instead of plugin object
 - Use `ProjectPermissionMixin` on project detail page (#350)
- **Timeline**
 - Use common pagination template (#336)

15.3.3 Fixed

- **Projectroles**
 - Output of template tag `get_project_link()`
 - Redundant inheritance in `CurrentUserFormMixin` (#12)
 - Trailing slashes not parsed correctly in remote project URLs (#319)
 - Crash in `get_project_column_count()` with no active project app plugins (#320)
 - UI test helper `build_selenium_url()` refactored to work with Chrome v77 (#337)
 - Disallow empty values in `RemoteSite.name`
 - Remote sync of parent category roles could fail with multiple subprojects
 - `RemoteProject` modifications not saved during sync update
 - Timeline events not created in remote project sync (#370)
 - DAL select modifying HTML body width (#365)
 - Footer overflow breaking layout (#367, #375)
- **Timeline**
 - Crash from exception raised by `get_object_link()` in a plugin (#328)

15.3.4 Removed

- **Projectroles**
 - Duplicate database indexes from `RoleAssignment` (#285)
 - Deprecated `get_setting()` tag from `projectroles_common_tags` (#283)
 - Project owner change from project updating form (#287)
 - `ProjectSettingMixin` from `projectroles.tests.test_views` (#357)

15.4 v0.6.2 (2019-06-21)

15.4.1 Added

- **General**
 - Badges for Readthedocs documentation and Zenodo DOI (#274)
- **Bgjobs**
 - `BackgroundJobFactory` for tests from Varfish-web
- **Projectroles**
 - Unit test to assure owner user creation during project update when using SODAR Taskflow (`sodar_taskflow#49`)
 - Common template tag `get_app_setting()` (#281)
 - Hiding app settings from forms with `user_modifiable` (#267)
 - `AppSetting.value_json` field (#268)

- **Sodarcache**
 - Logging in `delete_cache()` (#279)
- **Userprofile**
 - Support for `AppSetting.user_modifiable` (#267)

15.4.2 Changed

- **General**
 - Upgrade minimum Django version to 1.11.21 (#278)
- **Projectroles**
 - `get_setting()` template tag renamed into `get_django_setting()` (#281)
 - Implement project app descriptions on details page with `get_info_link()` (#277)

15.4.3 Fixed

- **General**
 - Documentation sections for Readthedocs

15.5 v0.6.1 (2019-06-05)

15.5.1 Added

- **Filesfolders**
 - Example project list columns (#265)
 - Setting `FILESFOLDERS_SHOW_LIST_COLUMNS` to manage example project list columns (#265)
- **Projectroles**
 - Optional project list columns for project apps (#265)
- **Sodarcache**
 - `delete_cache()` API function (#257)

15.5.2 Changed

- **Projectroles**
 - Refactor `RemoteProject.get_project()` (#262)
 - Use `get_info_link()` in remote site list (#264)
 - Define `SYSTEM_USER_GROUP` in `SODAR_CONSTANTS` (#251)
 - Make pagedown textarea element resizeable and increase minimum height (#273)
- **Sodarcache**
 - Handle and log raised exceptions in `synccache` management command (#272)

- **Userprofile**
 - Disable user settings link if no settings are available (#260)

15.5.3 Fixed

- **General**
 - Chrome and Chromedriver version mismatch in Travis-CI config (#254)
- **Projectroles**
 - Remove redundant `get_project_list()` call from `project_detail.html`

15.5.4 Removed

- **Projectroles**
 - Unused project statistics in the home view (#269)
 - App settings deprecation protection (#245)
- **Sodarcache**
 - Unused `TaskflowCacheUpdateAPIView` (#205)

15.6 v0.6.0 (2019-05-10)

15.6.1 Added

- **Filesfolders**
 - Provide app statistics for siteinfo (#18)
- **Projectroles**
 - User settings for settings linked to users instead of projects (#16)
 - `user_settings` field in project plugins (#16)
 - Optional `label` key for settings
 - Optional “wait for element” args in UI test helpers to ease Javascript testing (#230)
 - `get_info_link()` template tag (#239)
 - `get_setting_defs()` API function for retrieving project and user setting definitions (#225)
 - `get_all_defaults()` API function for retrieving all default setting values (#225)
 - Human readable labels for app settings (#9)
- **Siteinfo**
 - Add app for site info and statistics (#18)
- **Sodarcache**
 - Optional `--project` argument for the `synccache` command (#232)
- **Timeline**

- Provide app statistics for siteinfo (#18)
- **Userprofiles**
 - View and form for displaying and updating user settings (#16)

15.6.2 Changed

- **General**
 - Upgrade to ChromeDriver v74 (#221)
- **Bgjobs**
 - Job order to match downstream Varfish
- **Filesfolders**
 - Update app settings (#246)
- **Projectroles**
 - Rename `project_settings` module to `app_settings` (#225)
 - App settings API updated to support project and user settings (#225)
 - Write an empty dict for `app_settings` by default

15.6.3 Fixed

- **Bgjobs**
 - Date formatting in templates (#220)
- **Sodarcache**
 - Crash from `__repr__()` if project not set (#223)
 - Broken backend plugin icon (#250)

15.6.4 Removed

- **Timeline**
 - Unused and deprecated project settings (#246)

15.7 v0.5.1 (2019-04-16)

15.7.1 Added

- **General**
 - Bgjobs/Celery updates from Kiosc (#175)
 - Default error templates in `projectroles/error/*.html` (#210)
- **Projectroles**
 - Optional `user` argument in `ProjectAppPlugin.update_cache()` (#203)

- Migration for missing `RemoteProject` foreign keys (#197)
- **Sodarcache**
 - API logging (#207)
 - Indexing of identifying fields (#218)

15.7.2 Changed

- **General**
 - Extend `projectroles/base.html` for all site app templates, update docs (#217)
 - Use `projectroles` error templates on the example site (#210)
- **Sodarcache**
 - Make `user` field optional in models and API (#204)
 - Rename app configuration into `SodarcacheConfig` to follow naming conventions (#202)
 - Rename `updatecache` management command to `synccache` (#208)

15.7.3 Fixed

- **General**
 - Add missing `curl` dependency in `install_os_dependencies.sh` (#211)
 - Django debug toolbar not displayed when using local configuration (#213)
- **Projectroles**
 - Nested app names not properly returned by `utils.get_app_names()` (#206)
 - Forced width set for all Bootstrap modals in `projectroles.css` (#209)
 - Long category paths breaking remote project list (#84)
 - Incorrect table rows displayed during project list initialization (#212)
 - Field `project` not set for source site `RemoteProject` objects (#197)
 - Crash from `project_base.html` in site app if not overriding title block (#216)

15.7.4 Removed

- **General**
 - Django debug toolbar workarounds from `project.css` and `project.scss` (#215)
- **Projectroles**
 - `PROJECTROLES_ADMIN_OWNER` deprecation protection: use
`PROJECTROLES_DEFAULT_ADMIN` (#190)

15.8 v0.5.0 (2019-04-03)

15.8.1 Added

- **Projectroles**
 - Warning when using an unsupported browser (#176)
 - Setting `PROJECTROLES_BROWSER_WARNING` for unsupported browser warning (#176)
 - Javascript-safe toggle for `get_setting()` template tag
 - ID attributes in site containers (#173)
 - Setting `PROJECTROLES_ALLOW_LOCAL_USERS` for showing and syncing non-LDAP users (#193)
 - Allow synchronizing existing local target users for remote projects (#192)
 - Allow selecting local users if in local user mode (#192)
 - `RemoteSite.get_url()` helper
 - Simple display of links to project on external sites in details page (#182)
- **Sodarcache**
 - Create app (#169)

15.8.2 Changed

- **General**
 - Upgrade to Bootstrap 4.3.1 and Popper 1.14.7 (#181)
- **Projectroles**
 - Improve remote project sync logging (#184, #185)
 - Rename `PROJECTROLES_ADMIN_OWNER` into `PROJECTROLES_DEFAULT_ADMIN` (#187)
 - Update login template and `get_login_info()` to support local user mode (#192)

15.8.3 Fixed

- **Projectroles**
 - Crash in `get_assignment()` if called with `AnonymousUser` (#174)
 - Line breaks in templates breaking `badge-group` elements (#180)
 - User autocomplete for users with no group (#199)

15.8.4 Removed

- **General**
 - Deprecated Bootstrap 4 workaround from `project.js` (#178)

15.9 v0.4.5 (2019-03-06)

15.9.1 Added

- **Projectroles**
 - User autocomplete widgets (#51)
 - Logging in `syncgroups` and `syncremote` management commands
 - `PROJECTROLES_DELEGATE_LIMIT` setting (#21)

15.9.2 Changed

- **General**
 - Upgrade minimum Django version to 1.11.20 (#152)
 - Use user autocomplete in forms in place of standard widget (#51)
- **Filesfolders**
 - Hide parent folder widgets in item creation forms (#159)
- **Projectroles**
 - Enable allowing multiple delegates per project (#21)

15.9.3 Fixed

- **Filesfolders**
 - File upload widget error not displayed without Bootstrap 4 workarounds (#164)
- **Projectroles**
 - Potential crash in `syncremote` if run as Celery job (#160)

15.9.4 Removed

- **General**
 - Old Bootstrap 4 workarounds for `django-crispy-forms` (#157)

15.10 v0.4.4 (2019-02-19)

15.10.1 Changed

- **Projectroles**
 - Modify `modifyCellOverflow()` to work with non-table containers (#149)
 - Non-Pagedown form textarea height no longer adjusted automatically (#151)

15.10.2 Fixed

- **Projectroles**
 - Crash in remote project sync caused by typo in `remoteproject_sync.html` (#148)
 - Textarea element CSS override breaking layout in third party components (#151)

15.11 v0.4.3 (2019-01-31)

15.11.1 Added

- **General**
 - Codacy badge in `README.rst` (#140)
- **Projectroles**
 - Category and project display name configuration via `SODAR_CONSTANTS` (#141)
 - `get_display_name()` utils function and template tag to retrieve `DISPLAY_NAMES` (#141)
 - Django admin link warning if `taskflowbackend` is enabled

15.11.2 Changed

- **General**
 - Use `get_display_name()` to display category/project type (#141)
- **Projectroles**
 - Hide immutable fields in forms (#142)
 - Rename Django admin link in user dropdown

15.11.3 Fixed

- **Projectroles**
 - View access control for categories (#143)

15.11.4 Removed

- **General**
 - Redundant `rules.is_superuser` predicates from rules (#138)
- **Projectroles**
 - `get_project_type()` template tag (use `get_display_name()` instead)
 - Unused template `_roleassignment_import.html`
 - `PROJECT_TYPE_CHOICES` from `SODAR_CONSTANTS`
 - `force_select_value()` helper no longer used in forms (#142)

15.12 v0.4.2 (2019-01-25)

15.12.1 Added

- **General**
 - Flake8 and Codacy coverage in Travis-CI (#122)
 - Flake8 in GitLab-CI (#127)
- **Projectroles**
 - Automatically pass CSRF token to unsafe Ajax HTTP methods (#116)
 - Queryset filtering in `ProjectPermissionMixin` from `digestiflow-web` (#134)
 - Check for `get_project_filter_key()` from `digestiflow-web` (#134)

15.12.2 Changed

- **General**
 - Upgrade minimum Django version to 1.11.18 (#120)
 - Upgrade Python dependencies (#123)
 - Update `.coveragerc`
 - Upgrade to Bootstrap 4.2.1 (#23)
 - Upgrade to JQuery 3.3.1 (#23)
 - General code cleanup
 - Code formatting with Black (#133)
- **Filesfolders**
 - Refactor `BatchEditView` and `FileForm.clean()` (#128)
- **Projectroles**
 - Use `alert-dismissible` to dismiss alerts (#13, #130)
 - Update `DataTables` dependency in `search.html` template
 - Refactor `ProjectModifyMixin` and `RemoteProjectAPI` (#128)
 - Disable `USE_I18N` in example site settings (#117)
 - Refactor `ProjectAccessMixin._get_project()` into `get_project()` (#134)
 - Rename `BaseAPIView` into `SODARAPIBaseView`
- **Timeline**
 - Refactor `get_event_description()` (#30, #128)

15.12.3 Fixed

- **General**
 - Django docs references (#131)

- **Projectroles**
 - `sodar-list-dropdown` layout broke down with Bootstrap 4.2.1 (#23)
 - `TASKFLOW_TEST_MODE` not checked for allowing SODAR Taskflow tests (#126)
 - Typo in `update_remote` timeline event description (#129)
 - Textarea height modification (#125)
 - Text wrapping in `sodar-list-btn` and `sodar-list-dropdown` with Bootstrap 4.2.1 (#132)
- **Taskflowbackend**
 - `TASKFLOW_TEST_MODE` not checked for allowing `cleanup()` (#126)
 - `FlowSubmitException` raised instead of `CleanupException` in `cleanup()`

15.12.4 Removed

- **General**
 - Legacy Python2 `super()` calls (#118)
- **Projectroles**
 - Custom alert dismissal script (#13)
- **Example Site App**
 - Example file `test.py`

15.13 v0.4.1 (2019-01-11)

15.13.1 Added

- **General**
 - Travis-CI configuration (#90)
- **Adminalerts**
 - Option to display alert to unauthenticated users with `require_auth` (#105)
- **Projectroles**
 - `TaskflowAPIAuthentication` for handling Taskflow API auth (#47)
 - Handle GET requests for Taskflow API views (#47)
 - API version settings `SODAR_API_ALLOWED_VERSIONS` and `SODAR_API_MEDIA_TYPE` (#111)
 - Site app support in `change_plugin_status()`
 - `get_sodar_constants()` helper (#112)
- **Taskflowbackend**
 - API logging

15.13.2 Changed

- **General**
 - Upgrade minimum Python version requirement to 3.6 (#102)
 - Update and cleanup Gitlab-CI setup (#85)
 - Update Chrome Driver for UI tests
 - Cleanup Chrome setup
 - Enable site message display in login view (#105)
 - Cleanup and refactoring for public GitHub release (#90)
 - Drop support for Ubuntu Jessie and Trusty
 - Update installation utility scripts (#90)
- **Filesfolders**
 - Move inline javascript into `filesfolders.js`
- **Projectroles**
 - Refactor `BaseTaskflowAPIView` (#47)
 - Rename Taskflow specific API views (#104)
 - Unify template tag names in `projectroles_tags`
 - Change default SODAR API media type into `application/vnd.bihealth.sodar-core+json` (#111)
 - Allow importing `SODAR_CONSTANTS` into settings for modification (#112)
 - Move `SODAR_CONSTANTS` to `constants.py` (#112)
- **Timeline**
 - Rename Taskflow specific API views (#104)

15.13.3 Fixed

- **Filesfolders**
 - Overwrite check for zip archive upload if unarchiving was unset (#113)
- **Projectroles**
 - Potential Django crash from auth failure in Taskflow API views
 - Timeline description for updating a remote project
 - Project update with Taskflow failure if description not set (#110)
- **Timeline**
 - `TaskflowEventStatusSetAPIView` skipping `sodar_token` check (#109)

15.13.4 Removed

- **Filesfolders**
 - Unused dropup app buttons mode in templates (#108)
- **Projectroles**
 - Unused arguments in email API
 - Unused static file shepherd-theme-default.css
 - Disabled role importing functionality (#61, pending #17)
 - Unused dropup app buttons mode in templates (#108)
- **Timeline**
 - `ProjectEventStatus.get_timestamp()` helper

15.14 v0.4.0 (2018-12-19)

15.14.1 Added

- **General**
 - `SODAR_API_DEFAULT_HOST` setting for server host for API View URLs (sodar#396)
- **Bgjobs**
 - Add app from varfish-web (#95)
- **Filesfolders**
 - Add app from sodar v0.4.0 (#86)
- **Projectroles**
 - Setting `PROJECTROLES_ENABLE_SEARCH` (#70)
 - Re-enable “home” link in project breadcrumb (#80)
 - `get_extra_data_link()` in `ProjectAppPluginPoint` for timeline extra data (#6)
 - Allow overriding project class in `ProjectAccessMixin`
 - Optional disabling of categories and nesting with `PROJECTROLES_DISABLE_CATEGORIES` (#87)
 - Optional hiding of apps from project menus using `PROJECTROLES_HIDE_APP_LINKS` (#92)
 - Secure SODAR Taskflow API views with `TASKFLOW_SODAR_SECRET` (#46)
- **Taskflowbackend**
 - `test_mode` flag configured with `TASKFLOW_TEST_MODE` in settings (#67)
 - Submit `sodar_secret` for securing Taskflow API views (#46)
- **Timeline**
 - Display of extra data using `{extra-NAME}` (see documentation) (#6)

15.14.2 Changed

- **General**
 - Improve list button and dropdown styles (#72)
 - Move pagedown CSS overrides into `projectroles.css`
 - Reduce default textarea height (#96)
- **Projectroles**
 - Make sidebar resizable in CSS (#71)
 - Disable search if `PROJECTROLES_ENABLE_SEARCH` is set `False` (#70)
 - Allow appending custom items in project breadcrumb with `nav_sub_project_extend` block (#78)
 - Allow replacing project breadcrumb with `nav_sub_project` block (#79)
 - Disable remote site access if `PROJECTROLES_DISABLE_CATEGORIES` is set (#87), pending #76
 - Disable access to invite views for remote projects (#89)
 - Set “project guest” as the default role for new members (#94)
 - Make noncritical settings variables optional (#14)

15.14.3 Fixed

- **General**
 - Potential inheritance issues in test classes (#74)
 - LDAP dependency script execution (#75)
- **Projectroles**
 - Long words in app names breaking sidebar (#71)
 - Member modification buttons visible for superuser in remote projects (#73)
 - Breadcrumb project detail link display issue in `base.html` (#77)
 - “None” string displayed for empty project description (#91)
 - Crash in search from empty project description

15.15 v0.3.0 (2018-10-26)

15.15.1 Added

- **General**
 - Test config and script for SODAR Taskflow testing
- **Adminalerts**
 - Add app based on SODAR v0.3.3 (#27)
 - `TASKFLOW_TARGETS` setting
- **Projectroles**

- RemoteSite and RemoteProject models (#3)
- RemoteSiteAppPlugin site plugin (#3)
- PROJECTROLES_SITE_MODE and PROJECTROLES_TARGET_CREATE settings (#3)
- Remote site and project management site app (#3)
- Remote project API (#3)
- Generic SODAR API base classes
- SodarUserMixin for SODAR user helpers in tests
- Optional readme and sodar_uuid args for _make_project() in tests
- syncremote management command for calling RemoteProjectAPI.sync_source_data()
- get_project_by_uuid() and get_user_by_username() template tags
- get_remote_icon() template tag (#3)
- Predicates in rules for handling remote projects (#3)
- ProjectModifyPermissionMixin for access control for remote projects (#3)
- is_remote() and get_source_site() helpers in the Project model (#3)
- Include template _titlebar_nav.html for additional title bar links
- **Taskflowbackend**
 - Add app based on SODAR v0.3.3 (#38)
- **Timeline**
 - RemoteSite model in api.get_event_description() (#3)

15.15.2 Changed

- **General**
 - Update documentation for v0.3 changes, projectroles usage and fixes to v0.2 docs (#26)
- **Adminalerts**
 - Make ADMINALERTS_PAGINATION setting optional
- **Projectroles**
 - Allow LoggedInPermissionMixin to work without a permission object for superusers
 - Enable short/full title selection and remote project icon in get_project_link() template tag
 - Refactor rules
 - Disable Taskflow API views if Taskflow backend is not enabled (#37)
 - DataTables CSS and JS includes loaded in the search template (#45)
- **Timeline**
 - Minor refactoring of api.get_event_description() (#30)

15.15.3 Fixed

- **General**
 - Pillow dependency typo in `requirements/base.txt` (#33)
 - Login page crash if `AUTH_LDAP*_DOMAIN_PRINTABLE` not found (#43)
- **Projectroles**
 - Sidebar create project visible for site apps if URL name was “create” (#36)
 - Enabling LDAP without a secondary backend caused a crash (#39)

15.15.4 Removed

- **General**
 - iRODS specific CSS classes from `projectroles.css`
 - App content width limit in `projectroles.css`
 - Domain-specific Login JQuery
 - DataTables CSS and JS includes from base template (#45)

15.16 v0.2.1 (2018-09-20)

15.16.1 Changed

- **General**
 - Change `omics_uuid` field in all apps’ models to `sodar_uuid` (sodar#166)
- **Projectroles**
 - Rename abstract `OmicsUser` model into `SODARUser` (sodar#166)
 - Rename `OMICS_CONSTANTS` into `SODAR_CONSTANTS` (sodar#166)
 - Rename the `omics_constant()` template tag into `sodar_constant()` (sodar#166)
 - Rename `omics_url` in `sodar_taskflow` tests to `sodar_url` (see `sodar_taskflow#36`)
 - Rename `shepherd-theme-omics.css` to `shepherd-theme-sodar.css` (sodar#166)

15.17 v0.2.0 (2018-09-19)

15.17.1 Added

- **General**
 - `example_backend_app` for a minimal backend app example
 - Backend app usage example in `example_project_app`
- **Timeline**
 - Add timeline app based on SODAR v0.3.2 (#2)

- App documentation

15.17.2 Changed

- **General**
 - Update integration documentation (#1)
 - Restructure documentation files and filenames for clarity
- **Timeline**
 - Update CSS classes and overrides
 - Rename list views to `list_project` and `list_objects`
 - Rename list template to `timeline.html`
 - Refactor `api.get_event_description()`
 - Make `TIMELINE_PAGINATION` optional
 - Improve exception messages in `api.add_event()`

15.17.3 Fixed

- **Timeline**
 - User model access in `timeline.api`
 - Misaligned back button (#4)
 - Deprecated CSS in main list
- **Projectroles**
 - Third party apps not correctly recognized in `get_app_names()`

15.18 v0.1.0 (2018-09-12)

15.18.1 Added

- **General**
 - Create app package for Projectroles and other reusable apps based on SODAR release v0.3.1
 - `example_project_app` to aid testing and work as a minimal example
 - `example_site_app` for demonstrating site apps
 - `SITE_TITLE` and `SITE_INSTANCE_TITLE` settings
 - `SITE_PACKAGE` setting for explicitly declaring site path for code
 - Documentation for integration and development
 - Separate LDAP config in `install_ldap_dependencies.sh` and `requirements/ldap.txt`
- **Projectroles**
 - `static_file_exists()` and `template_exists()` helpers in common template tags

- Abstract OmicsUser model
 - `get_full_name()` in abstract OmicsUser model
 - `auth_backends.py` file for LDAP backends (sodar#132)
 - Versioneer versioning
 - `core_version()` in common template tags
 - Check for footer content in `include/_footer.html`
 - Example of the site base template in `projectroles/base_site.html`
 - Example of project footer in `projectroles/_footer.html`
- **Userprofile**
 - Add site app `userprofile` with user details
 - Display user UUID in user profile

15.18.2 Changed

- **Projectroles**
 - Move custom modal into `projectroles/_modal.html`
 - Check for `user.name` in user dropdown
 - Move content block structure and sidebar inside `projectroles/base.html`
 - Move site title bar into optional include template `projectroles/_site_titlebar.html`
 - Move search form into optional include template `projectroles/_site_titlebar_search.html`
 - Make title bar dropdown includeable as `_site_titlebar_dropdown.html`
 - Title bar CSS and layout tweaks
 - Move `search.js` under `projectroles`
 - Move `projectroles` specific javascript into `projectroles.js`
 - Move `site_version()` into common template tags
 - Move title bar admin and site app links to user dropdown (sodar#342)
 - Move project specific CSS into optionally includable `projectroles.css`
 - Refactor and cleanup CSS
 - Move `set_user_group()` into `projectroles.utils`
 - Move `syncgroups` management command into `projectroles`
 - Copy improved multi LDAP backend setup from `flowcelltool` (sodar#132)
 - Move LDAP authentication backends into `projectroles` (sodar#132)
 - Move `login.html` into `projectroles`
 - Display `SITE_INSTANCE_TITLE` in email instead of a hardcoded string
 - Display the first contact in `settings.ADMINS` in email footer
 - Use `get_full_name()` in email sending

- Get site version using `SITE_PACKAGE`
- Get LDAP domain names to login template from settings
- Rename custom CSS classes and HTML IDs from `omics-*` into `sodar-*` (sodar#166)
- Move Shepherd theme CSS files into `projectroles`

15.18.3 Fixed

- **Projectroles**

- Tests referring to the `filesfolders` app not included in this project
- `TestHomeView.test_render()` assumed extra SODAR system user was present (see sodar#367)
- Tour link setup placing

- **Userprofile**

- Missing user name if name field not filled in `user_detail.html`

15.18.4 Removed

- **Projectroles**

- Deprecated Javascript variables `popupWaitHtml` and `popupNoFilesHtml`
- Unused template `irods_info.html`

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

p

`projectroles.models`, [38](#)
`projectroles.plugins`, [35](#)
`projectroles.templatetags.projectroles_common_tags`,
 [45](#)
`projectroles.utils`, [47](#)

s

`sodarcache.models`, [65](#)

t

`timeline.models`, [77](#)

A

active (*projectroles.models.ProjectInvite* attribute), 40
 add_event() (*timeline.api.TimelineAPI* static method), 76
 add_object() (*timeline.models.ProjectEvent* method), 77
 app (*timeline.models.ProjectEvent* attribute), 77
 App Plugin, 7
 App Settings, 7
 app_name (*sodarcache.models.BaseCacheItem* attribute), 65
 app_permission (*projectroles.plugins.RemoteSiteAppPlugin* attribute), 37
 app_plugin (*projectroles.models.AppSetting* attribute), 38
 AppSetting (class in *projectroles.models*), 38
 AppSetting.DoesNotExist, 38
 AppSetting.MultipleObjectsReturned, 38
 AppSettingAPI (class in *projectroles.app_settings*), 43
 AppSettingManager (class in *projectroles.models*), 39
 assign_user_group() (in module *projectroles.models*), 43

B

Backend App, 7
 BackendPluginPoint (class in *projectroles.plugins*), 35
 BaseCacheItem (class in *sodarcache.models*), 65
 build_invite_url() (in module *projectroles.utils*), 47
 build_secret() (in module *projectroles.utils*), 47

C

change_plugin_status() (in module *projectroles.plugins*), 37
 check_backend() (in module *projectroles.templatetags.projectroles_common_tags*), 45

classified (*timeline.models.ProjectEvent* attribute), 77
 cleanup() (*taskflowbackend.api.TaskflowAPI* method), 68
 core_version() (in module *projectroles.templatetags.projectroles_common_tags*), 45

D

data (*sodarcache.models.JSONCacheItem* attribute), 66
 date_access (*projectroles.models.RemoteProject* attribute), 41
 date_created (*projectroles.models.ProjectInvite* attribute), 40
 date_expire (*projectroles.models.ProjectInvite* attribute), 40
 date_modified (*sodarcache.models.BaseCacheItem* attribute), 65
 delete_cache() (*sodarcache.api.SodarCacheAPI* class method), 64
 description (*projectroles.models.Project* attribute), 39
 description (*projectroles.models.RemoteSite* attribute), 42
 description (*projectroles.models.Role* attribute), 42
 description (*projectroles.plugins.RemoteSiteAppPlugin* attribute), 37
 description (*timeline.models.ProjectEvent* attribute), 77
 description (*timeline.models.ProjectEventStatus* attribute), 78
 Django App, 7
 Django Settings, 7
 Django Site, 7

E

email (*projectroles.models.ProjectInvite* attribute), 40
 entry_point_url_id (*projectroles.plugins.RemoteSiteAppPlugin* attribute), 37
 event (*timeline.models.ProjectEventObjectRef* attribute), 78

event (*timeline.models.ProjectEventStatus* attribute), 79
event_name (*timeline.models.ProjectEvent* attribute), 77
extra_data (*timeline.models.ProjectEvent* attribute), 77
extra_data (*timeline.models.ProjectEventObjectRef* attribute), 78
extra_data (*timeline.models.ProjectEventStatus* attribute), 79

F

find() (*projectroles.models.ProjectManager* method), 41
force_wrap() (in module *projectroles.templatetags.projectroles_common_tags*), 45

G

get_access_date() (*projectroles.models.RemoteSite* method), 42
get_active_plugins() (in module *projectroles.plugins*), 38
get_all_defaults() (*projectroles.app_settings.AppSettingAPI* class method), 43
get_all_settings() (*projectroles.app_settings.AppSettingAPI* class method), 43
get_api() (*projectroles.plugins.BackendPluginPoint* method), 35
get_app_names() (in module *projectroles.utils*), 47
get_app_plugin() (in module *projectroles.plugins*), 38
get_app_setting() (in module *projectroles.templatetags.projectroles_common_tags*), 45
get_app_setting() (*projectroles.app_settings.AppSettingAPI* class method), 44
get_assignment() (*projectroles.models.RoleAssignmentManager* method), 43
get_backend_api() (in module *projectroles.plugins*), 38
get_backend_include() (in module *projectroles.templatetags.projectroles_common_tags*), 45
get_cache_item() (*sodarcache.api.SodarCacheAPI* class method), 64
get_children() (*projectroles.models.Project* method), 39
get_class() (in module *projectroles.templatetags.projectroles_common_tags*),

45
get_current_status() (*timeline.models.ProjectEvent* method), 77
get_default_setting() (*projectroles.app_settings.AppSettingAPI* class method), 44
get_delegates() (*projectroles.models.Project* method), 39
get_depth() (*projectroles.models.Project* method), 39
get_display_name() (in module *projectroles.templatetags.projectroles_common_tags*), 46
get_display_name() (in module *projectroles.utils*), 47
get_django_setting() (in module *projectroles.templatetags.projectroles_common_tags*), 46
get_error_msg() (*taskflowbackend.api.TaskflowAPI* method), 69
get_event_description() (*timeline.api.TimelineAPI* static method), 76
get_expiry_date() (in module *projectroles.utils*), 47
get_extra_data_link() (*projectroles.plugins.ProjectAppPluginPoint* method), 36
get_full_name() (*projectroles.models.SODARUser* method), 43
get_full_title() (*projectroles.models.Project* method), 39
get_full_url() (in module *projectroles.templatetags.projectroles_common_tags*), 46
get_history_dropdown() (in module *projectroles.templatetags.projectroles_common_tags*), 46
get_info_link() (in module *projectroles.templatetags.projectroles_common_tags*), 46
get_members() (*projectroles.models.Project* method), 39
get_messages() (*projectroles.plugins.SiteAppPluginPoint* method), 37
get_object() (*projectroles.plugins.ProjectAppPluginPoint* method), 36
get_object_events() (*timeline.models.ProjectEventManager* method), 78
get_object_link() (*projectroles.plugins.ProjectAppPluginPoint* method), 36

`get_object_link()` (*timeline.api.TimelineAPI static method*), 76
`get_object_url()` (*timeline.api.TimelineAPI static method*), 76
`get_owner()` (*projectroles.models.Project method*), 40
`get_parents()` (*projectroles.models.Project method*), 40
`get_project()` (*projectroles.models.RemoteProject method*), 41
`get_project_by_uuid()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_project_cache()` (*sodarcache.api.SodaCacheAPI class method*), 64
`get_project_events()` (*timeline.api.TimelineAPI static method*), 76
`get_project_link()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_project_list_value()` (*projectroles.plugins.ProjectAppPluginPoint method*), 36
`get_project_title_html()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_remote_icon()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_setting_def()` (*projectroles.app_settings.AppSettingAPI class method*), 44
`get_setting_defs()` (*projectroles.app_settings.AppSettingAPI class method*), 44
`get_setting_value()` (*projectroles.models.AppSettingManager method*), 39
`get_source_site()` (*projectroles.models.Project method*), 40
`get_statistics()` (*projectroles.plugins.BackendPluginPoint method*), 36
`get_statistics()` (*projectroles.plugins.ProjectAppPluginPoint method*), 36
`get_status_changes()` (*timeline.models.ProjectEvent method*), 77
`get_taskflow_sync_data()` (*projectroles.plugins.ProjectAppPluginPoint method*), 36
`get_timestamp()` (*timeline.models.ProjectEvent method*), 77
`get_update_time()` (*sodarcache.api.SodaCacheAPI class method*), 64
`get_url()` (*projectroles.models.RemoteSite method*), 42
`get_user_by_username()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_user_display_name()` (*in module projectroles.utils*), 47
`get_user_html()` (*in module projectroles.templatetags.projectroles_common_tags*), 46
`get_value()` (*projectroles.models.AppSetting method*), 38
`get_visible_projects()` (*in module projectroles.templatetags.projectroles_common_tags*), 46

H

`handle_ldap_login()` (*in module projectroles.models*), 43
`has_role()` (*projectroles.models.Project method*), 40
`highlight_search_term()` (*in module projectroles.templatetags.projectroles_common_tags*), 46

I

`icon` (*projectroles.plugins.RemoteSiteAppPlugin attribute*), 37
`is_remote()` (*projectroles.models.Project method*), 40
`is_revoked()` (*projectroles.models.Project method*), 40
`issuer` (*projectroles.models.ProjectInvite attribute*), 40

J

`JSONCacheItem` (*class in sodarcache.models*), 65
`JSONCacheItem.DoesNotExist`, 65
`JSONCacheItem.MultipleObjectsReturned`, 66

L

`label` (*timeline.models.ProjectEventObjectRef attribute*), 78
`level` (*projectroles.models.RemoteProject attribute*), 41

M

`message` (*projectroles.models.ProjectInvite attribute*), 40
`mode` (*projectroles.models.RemoteSite attribute*), 42

N

`name` (*projectroles.models.AppSetting attribute*), 38

name (*projectroles.models.ProjectUserTag* attribute), 41
 name (*projectroles.models.RemoteSite* attribute), 42
 name (*projectroles.models.Role* attribute), 42
 name (*projectroles.plugins.RemoteSiteAppPlugin* attribute), 37
 name (*sodarcache.models.BaseCacheItem* attribute), 65
 name (*timeline.models.ProjectEventObjectRef* attribute), 78

O

object_model (*timeline.models.ProjectEventObjectRef* attribute), 78
 object_uuid (*timeline.models.ProjectEventObjectRef* attribute), 78

P

parent (*projectroles.models.Project* attribute), 40
 Peer Site, 7
 Project (*class in projectroles.models*), 39
 project (*projectroles.models.AppSetting* attribute), 38
 project (*projectroles.models.ProjectInvite* attribute), 41
 project (*projectroles.models.ProjectUserTag* attribute), 41
 project (*projectroles.models.RemoteProject* attribute), 41
 project (*projectroles.models.RoleAssignment* attribute), 42
 project (*sodarcache.models.BaseCacheItem* attribute), 65
 project (*timeline.models.ProjectEvent* attribute), 77
 Project App, 7
 Project.DoesNotExist, 39
 Project.MultipleObjectsReturned, 39
 project_uuid (*projectroles.models.RemoteProject* attribute), 41
 ProjectAppPluginPoint (*class in projectroles.plugins*), 36
 ProjectEvent (*class in timeline.models*), 77
 ProjectEvent.DoesNotExist, 77
 ProjectEvent.MultipleObjectsReturned, 77
 ProjectEventManager (*class in timeline.models*), 78
 ProjectEventObjectRef (*class in timeline.models*), 78
 ProjectEventObjectRef.DoesNotExist, 78
 ProjectEventObjectRef.MultipleObjectsReturned, 78
 ProjectEventStatus (*class in timeline.models*), 78
 ProjectEventStatus.DoesNotExist, 78
 ProjectEventStatus.MultipleObjectsReturned, 78

ProjectInvite (*class in projectroles.models*), 40
 ProjectInvite.DoesNotExist, 40
 ProjectInvite.MultipleObjectsReturned, 40
 ProjectManager (*class in projectroles.models*), 41
 projectroles.models (*module*), 38
 projectroles.plugins (*module*), 35
 projectroles.templatetags.projectroles_common_tags (*module*), 45
 projectroles.utils (*module*), 47
 ProjectUserTag (*class in projectroles.models*), 41
 ProjectUserTag.DoesNotExist, 41
 ProjectUserTag.MultipleObjectsReturned, 41

R

readme (*projectroles.models.Project* attribute), 40
 RemoteProject (*class in projectroles.models*), 41
 RemoteProject.DoesNotExist, 41
 RemoteProject.MultipleObjectsReturned, 41
 RemoteSite (*class in projectroles.models*), 42
 RemoteSite.DoesNotExist, 42
 RemoteSite.MultipleObjectsReturned, 42
 RemoteSiteAppPlugin (*class in projectroles.plugins*), 37
 render_markdown() (*in module projectroles.templatetags.projectroles_common_tags*), 46
 Role (*class in projectroles.models*), 42
 role (*projectroles.models.ProjectInvite* attribute), 41
 role (*projectroles.models.RoleAssignment* attribute), 43
 Role.DoesNotExist, 42
 Role.MultipleObjectsReturned, 42
 RoleAssignment (*class in projectroles.models*), 42
 RoleAssignment.DoesNotExist, 42
 RoleAssignment.MultipleObjectsReturned, 42
 RoleAssignmentManager (*class in projectroles.models*), 43

S

save() (*projectroles.models.AppSetting* method), 39
 save() (*projectroles.models.Project* method), 40
 save() (*projectroles.models.RemoteSite* method), 42
 save() (*projectroles.models.RoleAssignment* method), 43
 search() (*projectroles.plugins.ProjectAppPluginPoint* method), 36
 secret (*projectroles.models.ProjectInvite* attribute), 41
 secret (*projectroles.models.RemoteSite* attribute), 42
 set_app_setting() (*projectroles.app_settings.AppSettingAPI* class method), 45

[set_cache_item\(\)](#) (*sodarcache.api.SodarCacheAPI class method*), 65
[set_status\(\)](#) (*timeline.models.ProjectEvent method*), 77
[set_user_group\(\)](#) (*in module projectroles.utils*), 47
[site](#) (*projectroles.models.RemoteProject attribute*), 41
[Site App](#), 7
[site_version\(\)](#) (*in module projectroles.templatetags.projectroles_common_tags*), 46
[SiteAppPluginPoint](#) (*class in projectroles.plugins*), 37
[SODAR](#), 7
[SODAR Core](#), 7
[SODAR Core App](#), 7
[SODAR Core Based Site](#), 7
[sodar_uuid](#) (*projectroles.models.AppSetting attribute*), 39
[sodar_uuid](#) (*projectroles.models.Project attribute*), 40
[sodar_uuid](#) (*projectroles.models.ProjectInvite attribute*), 41
[sodar_uuid](#) (*projectroles.models.ProjectUserTag attribute*), 41
[sodar_uuid](#) (*projectroles.models.RemoteProject attribute*), 42
[sodar_uuid](#) (*projectroles.models.RemoteSite attribute*), 42
[sodar_uuid](#) (*projectroles.models.RoleAssignment attribute*), 43
[sodar_uuid](#) (*projectroles.models.SODARUser attribute*), 43
[sodar_uuid](#) (*sodarcache.models.BaseCacheItem attribute*), 65
[sodar_uuid](#) (*timeline.models.ProjectEvent attribute*), 78
[sodarcache.models](#) (*module*), 65
[SodarCacheAPI](#) (*class in sodarcache.api*), 64
[SODARUser](#) (*class in projectroles.models*), 43
[Source Site](#), 7
[static_file_exists\(\)](#) (*in module projectroles.templatetags.projectroles_common_tags*), 46
[status_type](#) (*timeline.models.ProjectEventStatus attribute*), 79
[submit\(\)](#) (*taskflowbackend.api.TaskflowAPI method*), 69
[submit_status](#) (*projectroles.models.Project attribute*), 40

T

[Target Site](#), 7
[TaskflowAPI](#) (*class in taskflowbackend.api*), 68
[TaskflowAPI.CleanupException](#), 68
[TaskflowAPI.FlowSubmitException](#), 68

[template_exists\(\)](#) (*in module projectroles.templatetags.projectroles_common_tags*), 47
[timeline.models](#) (*module*), 77
[TimelineAPI](#) (*class in timeline.api*), 75
[timestamp](#) (*timeline.models.ProjectEventStatus attribute*), 79
[title](#) (*projectroles.models.Project attribute*), 40
[title](#) (*projectroles.plugins.RemoteSiteAppPlugin attribute*), 37
[type](#) (*projectroles.models.AppSetting attribute*), 39
[type](#) (*projectroles.models.Project attribute*), 40

U

[update_cache\(\)](#) (*projectroles.plugins.ProjectAppPluginPoint method*), 37
[update_cache\(\)](#) (*sodarcache.api.SodarCacheAPI class method*), 65
[url](#) (*projectroles.models.RemoteSite attribute*), 42
[urls](#) (*projectroles.plugins.ProjectAppPluginPoint attribute*), 37
[urls](#) (*projectroles.plugins.RemoteSiteAppPlugin attribute*), 37
[use_taskflow\(\)](#) (*taskflowbackend.api.TaskflowAPI method*), 69
[user](#) (*projectroles.models.AppSetting attribute*), 39
[user](#) (*projectroles.models.ProjectUserTag attribute*), 41
[user](#) (*projectroles.models.RoleAssignment attribute*), 43
[user](#) (*sodarcache.models.BaseCacheItem attribute*), 65
[user](#) (*timeline.models.ProjectEvent attribute*), 78
[user_display](#) (*projectroles.models.RemoteSite attribute*), 42
[user_modifiable](#) (*projectroles.models.AppSetting attribute*), 39

V

[validate_setting\(\)](#) (*projectroles.app_settings.AppSettingAPI class method*), 45
[value](#) (*projectroles.models.AppSetting attribute*), 39
[value_json](#) (*projectroles.models.AppSetting attribute*), 39